



Download from Www.Somanuals.com. All Manuals Search And Download.

SPECIFICATIONS Indoor Temperature

Proposed operating range

23.0°F to 122.0°F :0.1°C/0.2°F Temperature resolution User-selectable (F° or C°) temperature display

: -5.0°C to +50.0°C/

Calendar and Clock

12/24 hour display in hh: mm format Date format: month - day format US Time Zone map Day of the week: User-selectable in three languages (English, Spanish or French) Dual 4 minute crescendo alarm with snooze Programmable snooze interval (one to 59 minutes) Moon Phase Backlight

Power

2 AAA size (UM-4) 1.5V batteries (not included) Dimensions 4.72(L) x 2.87(H) x 1.65(D) inches

WWVB RADIO CONTROLLED TIME

The NIST (National Institute of Standards and Technology) radio station (WWVB) is located in Ft. Collins, Colorado. It transmits an exact time signal continuously throughout the most of the continental United States at 60 KHz frequency. The Travel Alarm Clock can receive this WWVB signal through the internal antenna from up to 2 000 miles away. Due to Clock can receive this WWVB signal through the internal antenna from up to 2,000 miles away. Due to the nature of the Earth's ionosphere, reception can be limited during the daylight hours. The radio controlled clock will search for an alternate station that receives the atomic time signal from the NIST Atomic clock in Boulder, Colorado. The WWVB tower icon on the unit's display will flash indicating a radio signal reception from the WWVB station. If the tower icon is not fully lit, or if the time and date an tot set automatically please consider the

and date are not set automatically, please consider the following:

- * During night-time hours, atmospheric disturbances are typically less severe and radio signal reception may improve. A single daily reception is sufficient enough to keep the clock accuracy within 1 second.
 * Make sure the unit is positioned at 8 feet (2 meters) distance from any interference source such as a TV, computer monitor, microwave, etc.
- computer monitor, microwave, etc. * Within concrete wall rooms such as basements or office buildings, the received signal may be weakened. Always place the Table Alarm Clock near the window for better reception.

10

DATEXX WARRANTY INFORMATION

TELEDEX Limited U.S.A. Warranty TELEDEX INC. warrants these products to the original purchaser to be free from defective material and workmanship. The product will be repaired or replaced at our option, for up to one year when returned with proof of purchase to the address below. Include a check or money order for

9

\$5.00 to cover postage. Warranty valid only in the U.S.A.

TELEDEX INC. 1 Atlas st. Kenilworth, NJ 07033

11

www.datexx.com

12

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com