



## WXGA Versatile Installation Projector

### FEATURES

- WXGA resolution (1280 x 800)
- 5100 ANSI Lumens and 10.000:1 contrast ratio
- DLP<sup>®</sup> and BrilliantColor<sup>™</sup> technologies for detailed image quality
- Centered lens for easy planning & installation
- 1,7x optical zoom and Manual horizontal and vertical lens shift
- HDMI and DVI-D connectors for high quality digital video signals
- HDBaseT interface with support for HD video, digital audio and control signals over standard CAT5e/6 LAN cable
- Digital vertical & horizontal keystone, warp and individual corner adjustments
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- PC-Free presentation using JPG picture reader from USB thumb drive
- Wireless presentation streaming with optional WiFi dongle
- Audio ready with 2 x 7W stereo speakers with Surround emulation, 3 x 3,5mm Jack inputs and 1 x 3,5mm jack out. 3.5mm Jack microphone input
- Built-in 12V trigger for screen and/or blinds control



# DW3321

## MULTIMEDIA

The DW3321 offers great features and performance combined with great installation flexibility. The 5,100 ANSI lumens make it bright enough for larger screens, and the wide screen WXGA native image resolution ensures that your content will be delivered with fidelity and sufficient detail for a wide range of applications. The 1,34-2,4:1 Throw Ratio makes it possible to install the projector in a wide range of distances, making installation planning easier whether you replace an older projector or making a new installation. The 1,7x zoom range and horizontal and vertical lens shift gives further flexibility when installing the projector. Features such as 3D, JPG reader and HDBaseT ensures the projector can handle modern signal inputs and features customers expect.



## SPECIFICATIONS



<b>Display Type</b>	Single 0.65" DLP Technology by TI
<b>Brightness</b>	5,100 ANSI Lumens
<b>Native Resolution</b>	WXGA (1280 x 800)
<b>Maximum Resolution</b>	WUXGA (1920x1200) @60Hz
<b>Contrast Ratio</b>	10,000:1
<b>Lamp Life and Type</b>	1,500/ 3500 Hours (Normal/Eco. Mode), 370W/ 280W Osram
<b>Throw Ratio</b>	1.32~2.24:1
<b>Image Size (Diagonal)</b>	21"~351"
<b>Projection Distance</b>	1~ 10m
<b>Projection Lens</b>	F=2.45~ 3.22, f=18.8mm~32mm
<b>Zoom Ratio</b>	1.7x
<b>Aspect Ratio</b>	16:10
<b>Offset (full image height)</b>	Manual Lens Shift
<b>Keystone Correction</b>	Vertical: +/-30°, Horizontal: +/- 25°
<b>Speakers</b>	7W RMS x 2
<b>3D Ready</b>	Yes (Supports DLP Link, Blu-ray 3D)
<b>Lens Shift Range</b>	Vertical: 105-141% Horizontal: +/-10.9%
<b>Video Compatibility</b>	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
<b>I/O Connection Ports</b>	VGA-In (2x), HDMI/MHL, HDMI v1.4b, DVI-D, Component (5 BNC) (RGBHV), Audio-In (RCA), Audio-In (Mini-Jack)(3x), VGA-Out (15pin D-Sub), Audio-Out (RCA), Audio-Out (Mini-Jack), 1 x RJ45 (Network), 1 x RJ45 (HDBaseT), IP Telnet Capable Over RJ-45, 12v Trigger (3.5mm mini-jack), RS-232, 3D-Sync Out, USB type A (2x) (1x JPG Reader, Wifi Dongle, 1x 5V, 2A Power Output), USB miniB (Display), USB B (Service Only), Microphone (Mini-Jack), Remote Jack wire remote 1 in, 1 out (passthrough)
<b>Projection Method</b>	Table Top, Ceiling Mount (Front or Rear)
<b>Security Solutions</b>	Kensington® Security Slot, Security Bar, Keypad Lock
<b>Dimensions (W x D x H)</b>	445 x 331 x 143 mm, (Height w/Foot 162 mm)
<b>Weight</b>	8,4 kg
<b>Noise Level</b>	39dB/33dB (Standard/Eco. Mode)
<b>Power</b>	AC Universal 100-240V/50-60hz, Consumption: 530W (Normal Mode) / 430W (Eco.Mode)
<b>Warranty</b>	3 years projector / 1 year on lamp or 1000 hours whichever comes first
<b>Standard Accesories</b>	AC Power Cord, VGA Cable, Remote Control, Filter, Documentation Kit
<b>Optional Accesories</b>	Replacement Lamp: 5811119760-SVV, Wireless USB Dongle
<b>UPC</b>	813097020321

© Copyright 2015 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc.

DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.

Vivitek EMEA, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands  
tel: +31 20 655 0960 | fax: +31 20 655 0999 | email: info@vivitek.eu

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>