

#### **AM/FM STEREO RECEIVER**

## DRA-775RD

### An Innovative Receiver That Does Just About **Everything, Including Multi Room Entertainment**

The DENON DRA-775RD receiver is a truly versatile component meeting today's increasingly complex A/V and pure audio system requirements. Not only does it deliver reliable high power and ensure high-quality sound, it also includes video input and output capabilities as well as DENON'S innovative Multi Room Music Entertainment System and easy-to-tune RDS broadcast reception capabilities. The Multi Room Music Entertainment System lets you set up an amp and speakers in a separate room, connect them to the DRA-775RD, and enjoy program sources independently of the listener in the main room. The remarkable DRA-775RD deserves a close look and a listen as the best possible solution for your audio/video system needs.



Multi Room Music Entertainment System / High-Quality Power Amplifier / Pure Current Power Supply / Radio Data System (RDS)









#### Powerful, Versatile Amplifier

#### **High-Quality Power Amplifier**

High-speed, high-power transistors employed in a rational circuit configuration reflect DENON'S advanced amplifier technology and ensure a very hefty, clean power output.

#### **Pure Current Power Supply**

The DRA-775RD is endowed with the same type of power supply circuitry as DENON'S best integrated amplifiers.

Known as the Pure Current Power Supply, it incorporates DENON'S original circuit and high-capacity transformer to suppress dynamic IM distortion by 60 dB, yielding high dynamic power.

#### Low-Impedance Speaker Drive

The power supply and power amplifier stage are designed to respond even to sudden dips in speaker impedance, so that the speaker drive remains stable under all load conditions.

#### **Discrete Chassis Construction**

The signal path in the DRA-775RD is kept as short as possible from input to output. The power amplifier section, which handles high-level signals, employs separate heat sinks in a totally separate symmetrical layout for the left and right channels. Power supply circuitry is located close to the respective destinations to further prevent signal losses and eliminate interference.

#### Frequency Synthesis Tuning

#### **RDS Tuning System**

The DRA-775RD offers four RDS features: RDS (station) Search, Program Type (PTY), Traffic Program Identification (TP), and Radio Text Message (RT).

RDS Search lets you search for stations currently broadcasting RDS signals. PTY lets you select from among 22 types of music and programs you want to listen to-such as Classical. Jazz, Rock. Top 40. News, Sports-and a station broadcasting the selected type is automatically tuned in. TP, when turned ON, automatically tunes to a station which is about to broadcast a traffic report. And RT receives and displays a message of up to 64 characters that the station tuned in is currently transmitting.

#### AM/FM 40 Station Random Preset Memory Tuning

The DRA-775RD offers random preset and recall of up to 40 stations. Tuning is as simple as pressing a button.

#### **Auto Preset Memory**

A maximum of 40 FM stations can be searched by the tuner and automatically stored into the preset memory. This feature is useful when you do not know all the frequencies of local stations.

#### Sophisticated Tuning Circuit Design

Thanks to the use of large-capacity microprocessor ICs in the tuning section, reception drift is a thing of the past. The DRA-775RD also has a 3-pole varactor diode in its front end to guarantee accurate input of station frequencies.

- Improved AM Reception
- Large New Fluorescent Display
  - Additional Conveniences
- Auto scanning of radio frequency bands
  - Fast up/down manual tuning
    - Manual step tuning
  - · Last-channel-tuned memory









#### Your Audio/Video Control Center

#### Video and VCR Terminals

Audio systems can be easily upgraded to include versatile reproduction from video as well as audio sources, because the DRA-775RD is also equipped with VDP, VCR and Video Aux input and output terminals.

#### Video Select Switch

The DRA-775RD's Video Select function lets you select the desired video sources independently on the audio sources.

#### Easy Simulcast Copy

This feature not only permits reception and recording of FM/TV simulcast programs onto videotape, but it can also be used to combine, for example, the sound from a CD with the picture from a video disc.

- Pre-Out, Main-In Jacks Rec Out Selector 3-Way Speaker Terminals Loudness Switch
  - Bass & Treble control Tone defeat Switch Muting Switch (Remote only)

#### Multi Room Music Entertainment System

#### Multi Source Function

The DRA-775RD's Multi Source function lets you select different audio or video sources for viewing or listening Different sources can thus be enjoyed in the main room and the second room simultaneously. This novel feature gives you considerable flexibility when setting up and enjoying your system with the DRA-775RD. The output level, adjustable by the remote commander, is as much as 1V, enough to operate the optional power amplifier placed in a second room.

#### **Equipped for Room-to-Room Remote Control**

Since A-B switching of speakers is possible by remote control, the DRA-775RD can be used in configuring a room-to-room remote control system by adding the optional RC-616/617S/617W/618. And because direct terminals for the RC-616 (IF Re-transmitter) are provided on the DRA-775RD, audio systems in locations that do not easily receive infrared based emissions can also be reliably operated.

By combining Room-to-Room control and the Multi Source function, you can select an audio or video source as well as adjust the volume level and tune in a broadcast station, all independently from a second room, even while the listener in the main room is enjoying a different program source.

#### **Remote Control Functions**


#### Integral System (IS) Remote Control Unit

The DRA-775RD includes Integral System (IS) Remote Control and it commands not only the receiver but can also operate the main functions of a DENON CD player and a cassette deck when they are included in the system.

#### Multi Source Remote Control Unit

In addition to the Integral System Remote Control, the DRA-775RD comes with the Multi Source Remote Control Unit, which operates the Multi Source Output and commands the receiver to select the function, tune the radio, and adjust the volume level from a second room.

• Switched AC Outlets • Motor-Driven Volume Control • A-B Speaker Switching • Last Function Memory





# Specifications DRA-775RD

Power	amp	lifier	Section	

rower Ampliner Section		
Rated output	90W + 90W	
	(8 ohms, 20 Hz - 20 kHz, THD 0.05 %)	
Total harmonic distortion	0.009%(-3dB at rated output, 8 ohms)	
Power bandwidth	5 Hz - 40 kHz (8 ohms, THD 0.15%)	
Frequency response	20 Hz - 50 kHz ± 1.5 dB (at 1W)	
Output impedance	0.1ohm (1 kHz)	
Preamplifier Section		
Input sensitivity/ Impedance	PHONO (MM): 2.5 mV/47 kohms	
	CD, TAPE, VDP, VCR, V-AUX :	
	150 mV/ 47 kohms	
Max. input level	PHONO MM 150 mV/1 kHz	
RIAA deviation	20 Hz - 20 kHz ± 0.5 dB	
Signal-to-noise ratio (A-weighted)	PHONO MM 86 dB (at 5mV input)	
	CD, TAPE, VDP, VCR, V-AUX : 100 dB	
Tone control	Bass 100 Hz ± 10 dB	
	Treble 10 kHz ± 10 dB	
Loudness control	100 Hz : + 10 dB, 10 kHz : + 7 dB	
	(at LOUDNESS "on" position)	
Video Section		
Input Terminal	VDP, VCR, V-AUX: 1 Vp-p / 75 ohms	
Output terminal	VCR, MONITOR, MULTI SOURCE: 1 Vp-p / 75 ohms	
FM Section		
Tuning frequency range	87.5 - 107.9 MHz	
Usable sensitivity	0.9 μV (10.3 dBf)	
S/N 50 dB sensitivity (µV at 75 ohms)	Mono : 1.6 μV (15.3 dBf)	
	Stereo : 23 μV (38.5 dBf)	
Signal-to-noise ratio (A-weighting)	Mono: 82 dB, Stereo: 78 dB	
Total harmonic distortion	Mono : 0.1%, Stereo : 0.15%	
Capture ratio	1.5 dB	
AM suppression	50 dB	
Image rejection	42 dB	
Effective selectivity	55 dB (± 400 kHz)	
Frequency response	30 Hz - 15 kHz, +0.2, -1.5 dB	
Stereo separation	40 dB (1 kHz)	
AM Section		
Tuning frequency range	ncy range 520 - 1710 kHz	
Usable sensitivity	18 μV	
Signal-to-noise ratio	55 dB	
General		
Power supply, Power consumption	AC 120 V, 60 Hz, 3.4 A	
Dimensions, Weight	434 (W) x 161 (H) x 416 (D) mm, 11.5 kg	
	17.1"(W) x 6.3" (H) x 16.4" (D), 25.0 lbs	

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com