

OPERATING SYSTEM

FORM FACTOR

DIMENSIONS WEIGHT

UPC

DIAMOND MULTIMEDIA - SPECIFICATION SHEET SKU SM56E BRAND Supra May 4, 2009 - 4:14 pm

| SKU | SM56E | |
|------------------------------|---|--|
| SYSTEM BUILDER SKU | | |
| PRODUCT | DIAMOND SupraMax External (Serial) 56K Modem | |
| | | |
| PRODUCT DETAILED DESCRIPTION | Faster Internet Connections • Receive Phone Calls While Online | |
| | Faster Download Speeds | |
| | Quicker Connect Speeds | |
| | Complete Internet & Fax Solution Controller-based modem for maximum performance | |
| | Controller-based modern for maximum performance | |
| | Diamond Supra unleashes the highest performance SupraMax modems with newly adopted ITU, V.92 and V.44 | |
| | compression standards. SupraMax gives you the advantages of extensive analog access to the Internet with an added boost of speed over earlier | |
| | standards. These improvements includes accelerated upstream data transfers (up to 40% faster), faster Internet dial-up | |
| | connection times using an intelligent start-up sequence, and advanced compression algorithms that let you send common | |
| | file type (such as HTML, e-mail, and executable files) more efficiently. The new Modem-On-Hold feature lets you receive incoming voice calls without dropping your current modem connections. And, because the SupraMax V.92 is backward compatible with V.90 and earlier standards, you can relax and enjoy faster Internet speeds without worry. (For more information on V.92 features, please see below.) | |
| | | |
| | | |
| | | |
| | WHAT IS V.92? | |
| | V.92 is an International Telecommunications Union (ITU) standard for analog modem connections, a new improvement over the existing V.90. Though the top speed for downloads is still 56K, V.92 has a number of enhancements. | |
| | WHAT FEATURES ARE INCLUDED IN V.92? | |
| | There are four important benefits to the V.92 standard; Quick Connect, Modem-on-hold, PCM upstream and V.44 data compression. | |
| | Quick Connect - by reducing the amount of time it takes for the modem and server to handshake, connect time is reduced dramatically. Instead of taking around 25 seconds to connect, this may be reduced to 8 seconds. | |
| | Modem-on-hold - the end user can put the modem on hold and stay connected to the Internet. The user can take an incoming voice call, or even place a call while still connected. When the call is through, the end user can resume Internet activities without having to re-dial and connect. | |
| | PCM upstream - increases maximum upload speed to 44 Kbps. | |
| | V.44 - a new standard for data compression specifically for HTML (normal website), text and other common file types, for faster downloads. Throughput can increase up to 30-40%. This will supercede the current V.42bis standard. | |
| | WHAT IS REQUIRED FOR V.92 AND V.44 | |
| | Your ISP carrier must provide support for V.92 and V.44 compression. Please consult with your ISP for details. | |
| PRODUCT FEATURES | | |
| | Full featured data/fax external modem | |
| | Send documents at high speeds to fax machines or fax- Supports V.92 for speeds up to 56,000 bit/s Sends and receives faxes with speeds up to 14,400 bit/s Top-rated communications and Internet access software | |
| | | |
| | | |
| | | |
| PRODUCT SPECIFICATIONS | V.90, V.92 ITU standard 56K | |
| | Data compression V.44. V.42bis and MNP5 | |
| | V.34 and backwards compatible protocols | |
| | • Fax speeds up to 14,400 bit/s, Group III, Class 1 | |
| | Error correction V.42 LAPM and MNP 4 | |
| SYSTEM REQUIREMENT | EXTERNAL POWER REQUIREMENT | |
| 0.0. <u></u> | CPU | AMD Athlon® or Intel ® Pentium ® 4 |
| | CPU SPEED | 486 MHZ |
| | MEMORY | N/A |
| | HARD DISK | 5mb |
| | SYSTEM BUS | SHID |
| | SLOT | N/A |
| | CHASSIS | N/A |
| | MONITOR | Digital flat-panel (DFP) displays or DVI-I Compatilbe or |
| | MONTON | digital CRT display or High-resolution VGA monitor |
| | INTERNET ACCESS | NO |
| | USB | NO |
| | CD DVD | YES |
| | POWER SUPPLY | N/A |
| | | |

[PRODUCT WEIGHT]: 0.45LBS [PRODUCT WITH CONTENT WEIGHT]: 2.0 LBS

[PRODUCT]: 11 13/16 X 9 1/8 X 3 1/8 [RETAIL BOX]: 11 13/16 X 9 1/8 X 3 1/8 [S BUILDER]: 12 X 7 1/4 X 2

WIN98SE WINME WIN2000 WINXP LINUX32 LINUX64

RETAIL PACKAGE UPC: 018258001045

N/A

PACKAGE CONTENT

- DIAMOND SUPRAMAX EXTERNAL (SERIAL) 56K MODEM
- QUICK START GUIDE
 INSTALL CD

PRODUCT WEBPAGE

http://www.diamondmm.com/SM56E.php

PRODUCT NOTES

California Health & Safety Notice: The solder used in this product contains lead, a chemical known to the State of California to cause birth defects and other reproductive harm. Please wash hands after handling internal components and circuit boards and avoid inhalation of fumes if heating the solder.

Diamond, Diamond Multimedia and Stealth are registered trademarks of Diamond Multimedia.
ATI, Graphics by ATI, and Radeon are trademarks of ATI Technologies, Inc.
All other trademarks are property of their respective owners.
© 2009 Diamond Multimedia. All rights reserved.

Diamond Multimedia 9650 DeSoto Ave Chatsworth, CA 91311 Tel: (818) 534-1414 Fax: (818) 773-9619 http://www.diamondmm.com

• TELEPHONE CABLE (RJ-11)

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com