

Digi Economy MicroHub

D A T A
S H E E T

Economical Ethernet MicroHubs

MIL-510H/910H



The Digi economy MicroHubs are designed to provide an easy, cost-effective way to connect users to a network. These hubs offer a number of features that make them ideal for network configurations ranging from workgroups to small offices.

The advantages begin with innovative engineering that combines “full-size” performance and functionality with a space-saving desktop or wall-mountable design.

For environments with small workgroups, select the Digi MIL-510H. Its five ports make it easy to interconnect up to five 10Base-T (RJ-45) segments.

The Digi MIL-910H is ideal for use as a workgroup hub or as an integral part of an enterprise network. It features eight 10Base-T (RJ-45) ports and one 10Base2 (BNC) port that provide greater flexibility for integrating UTP and thin coax network environments.

On both models the first port is switch selectable so it can function as a standard hub port or as a cascade port to connect up to four hubs. The 10Base2 connection on the MIL-910H can be utilized to cascade up to 30 hubs.

They support auto-partitioning and reconnection which allow the hubs to isolate faulty segments and disable/enable the appropriate port. This ensures that additional collisions do not occur. The hubs are also equipped with an array of LEDs that provide simple network diagnosis coupled with “at-a-glance” convenience.

The MIL-510H and MIL-910H are also available in International versions, designated with the suffix IN. Power supplies compatible with the country’s power requirements are provided.

The Digi MIL-510H and MIL-910H are backed by Digi’s legendary service and support package featuring a five-year warranty and expert telephone technical support.

- Digi MIL-510H interconnects five 10BaseT segments
- MIL-910H interconnects one 10Base2 and eight 10BaseT segments
- Sleek design with full functionality
- 5 year warranty



Features/Specifications

Features

- 510H provides five 10Base-T ports
- 910H provides one 10Base2 segment and 8 10Base-T ports
- Support auto-partitioning and reconnection capability
- Support 10 Mbps transmission rates
- Use one RJ-45 port as cascading port; 910H can also use the BNC port for cascading
- Two diagnostic LEDs per port show Link/Receive and Polarity/Partition
- Power and Collision LED indicators; 910H also have indicator for BNC port cascade status
- IEEE 802.3 compliant
- Wall mountable hardware included

Product Package

- Install Guide
- 110 to 220 VDC power adapter

Electrical

- Input: 110/220VAC
- Output: 220VAC at 60hz (Int) 7.5VDC 1 amp 60hz (U.S.)

Standards Compliance

- FCC A
- UL 1950
- CSA 22.2 No.950
- EN 60950
- CE
 - EN55022
 - EN50082

Environmental

- Operating temperature: 50°F to 113°F (10°C to 45°C)
- Relative humidity: 10% to 90% non-condensing
- Altitude: 0 to 12,000 ft (0 to 3,660 m)

Physical LAN Interface

- MIL-510H: 5 RJ-45 connectors
- MIL-910H: 8 RJ-45 connectors and one BNC connector (10Base2)

Digi Service And Support

You can purchase with confidence knowing that Digi is here to support you with expert technical support, the industry's strongest warranty (five full years) and a 30 day money-back guarantee.

Digi International Corporate:

11001 Bren Road East
 Minnetonka, MN 55343
 Tel: 1-800-344-4273
 612-912-3444
 FAX: (612) 912-4952
 E-Mail: info@dgii.com
 Web: www.dgii.com

Regional Sales ofices

Minnesota: 1-800-344-4273
 California: 1-800-466-4526
 Ohio: 1-800-782-7428
 Tennessee: 1-800-366-8844
 Virginia: (703) 553-2560

International Sales offices:

Denmark: +45 49 17 70 90
 France: +33 1 46 40 39 20
 Germany: +49 221 920 520
 The Netherlands: +31 20 5207 566
 United Kingdom: +44 1276 853 600
 Australia: +61 2 96 80 8944
 Hong Kong: +852 2833 1008
 Singapore: +65 732 1318
 Email: europa@dgii.com
latinamerican@dgii.com
pacificrim@dgii.com

Dimensions

MIL-510H Height	Width	Depth	Weight
.98 in. (2.5cm)	4.92 (12.5 cm)	2.59 in.(6.6 cm)	Unit 2 oz. (.056 Kg)

MIL-910H Height	Width	Depth	Weight
1.25 in. (3.2cm)	7.22 in. (18.5 cm)	3.93 in.(10 cm)	Unit 4 oz. (.112 Kg)

Models and Part Numbers

MIL-510H MicroHub (110V power supply)MIL-510H
 MIL-510H MicroHub (220V power supply)MIL-510HIN
 MIL-910H MicroHub (110V power supply)MIL-910H
 MIL-910H MicroHub (220V power supply)MIL-910HIN

© 1998 Digi International. All rights reserved. The Digi logo is a registered trademark of Digi International. All other brand names and product names are trademarks or registered trademarks of their respective holders. GSA: GS-35F-3395D.



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>