

UNLEASH THE PERFORMANCE AND POWER 5" PTO & Towable Chipper/Shredder!



The model SC5540 (70554) with the 70487 one-speed blower attachment makes chip placement easy.

ModelSC5540(70554)

Model	Engine (LxWxH)	Size	Chipper Capacity	Chipper Shredder	Weight (Lbs.)	3 Point Hitch	PTO	Tires
SC5540 (70554)	PTO	42"x42"x48"	5"	4 chipper blades 36 shredding knives	450	Cat. 1	540 rpm	
SC5614 (71020)	Honda 614cc	80"x46"x50"	5"	4 chipper blades 36 shredding knives	715			480/4000-8 pneumatic
Options: 70487 70649 71110 71125	Leaf Tamper Two Speed B	lower with 8-Blade F	Radial Fan; 360 d	egree rotation of 4" Discharge egree rotation of 6" Discharge with Aluminum Handle				

* 71125 Vacuum Hose Attachment works exclusively with 71110 2-speed blower. **Model 70554 - Tractor with 540 rpm PTO drive hp rating



Find a dealer near you!

Call us at 800.247.7335 or Log onto www.BearCatProducts.com

> P.O. Box 849, West Fargo, ND 58078 Email: sales@BearCatProducts.com Fax: 701.282.9522



5" PTO & Towable Chipper/Shredder Specs

Models SC5540 (70554), SC5614 (71020)

SHREDDING EFFICIENCY

36 serrated, free-swinging shredding knives are heat-treated for strength and durability.

ROTOR

125 lbs. [57kg], dynamically balanced .75" [1.9cm] thick steel face plate, 18" [45.7cm] in diameter, turning 2000 rpm's.

FOUR CHIPPING BLADES

- High chrome content reversible, heat-treated chipper steel blades [3.125" x 2" x .25"] mounted 90 degrees to each other for smoother operation, less vibration and longer blade edge life.
- Quickly chip limbs up to 5" [12.7cm] in diameter.

MODEL SC5614 (71020) - HONDA 614cc ENGINE

• Road towable with 40.5" [103cm] wheel base with 480/400x8 pneumatic tires.

MODEL SC5540 (70554) - PTO DRIVEN

FUEL CAPACITY

SC5614 (71020) 614cc has 6.6 gallon [25 liter] separate fuel tank.

SHREDDER AND CHIPPER

- Shredder Hopper is 30" x 20" [76cm x 51cm] with a 12" wide throat.
- Chipper Capacity has 5" [12.7cm] for branches and limbs.

HEAVY-DUTY. BUILT TO LAST

 Using 7 gauge (3/16" thick) [4.55mm] steel, 75" [1.9cm] thick steel flywheel, discharge screen is .25" [6.35mm] thick steel.

MANUAL BELT ENGAGEMENT - ON MODEL SC5614 (71020)

FEED OPENING

6.5" X 13.5" [16.5cm x 91.4cm]

DIAMOND SHAPED CHIPPING CHUTE

- 16" [40.6cm] long chute enables you to insert more irregular limbs, even if they have some knobs on them.
- 8" [20.3cm] from the bottom of the V to the top.

ADJUSTABLE AXLE MODEL SC5614 (71020)

Allows more weight on the tongue. Use when blower is attached.

WEIGHTS

- Model SC5614 (71020) weighs 715 lbs. [324kg].
- Model SC5540 (70554) PTO weighs 450 lbs. [204kg].

SAFETY

· Meets all applicable ANSI safety standards.

OPTIONS:

- 70487 One Speed Blower with 4-blade radial fan
- 70649 Leaf Tamper
- 71110 Two Speed Blower with 8-blade radial fan
- 71125 Vacuum Hose Attachment



Find a dealer near you!

Call us at 800.247.7335 or Log onto www.BearCatProducts.com Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com