

PERFECT SIZE FOR ALL APPLICATIONS 4" PTO & Towable Chippers!





Heavy duty rotor disc that features two reversible heat treated steel chipper blades



Convenient foot pedal releases tension from the belts acting as a starting aid.



Model	Engine	Size (LxWxH)	Chipper Capacity	Feed Opening Size	Start	Weight (Lbs.)	3 Point Hitch	Tires/Wheels
CH4614 (73420)	HONDA OHV	73" x 52" x 87"	4"	5.5" x 7"	Electric	820		5.3"x12" pneumatic
CH4540 (73454)	PTO Cat. 1 540 rpm	48" x 45" x 87"	4"	5.5" x 7"	N/A	600	Cat. 1	N/A

Accessory:

70454 LIGHT KIT FOR TOWING *AVAILABLE FOR ONLY CH4614



Find a dealer near you!

Call us at 800.247.7335 or Log onto www.BearCatProducts.com

P.O. Box 849, West Fargo, ND 58078 Email: sales@BearCatProducts.com bad. Fax: 701.282.9522



4" Chipper Specs

1. 20" [51CM] DIAMETER DISC

• 20" [51cm] x 1.25" [3.175cm] thick rotor disc weighs 140 lbs. [63.5kg], machine balanced.

2. HONDA ENGINE OVERHEAD VALVE

• 614cc Honda OHV Engine with electric start (battery not included)

3. PTO DRIVEN MODEL # CH4540 (73454)

• Is a PTO drive, category one 3-point that weighs 600 lbs. [272kg].

4. DOUBLE BANDED BELT DRIVE

5. FOUR CHIPPING BLADES

• Both have the same reversible chipper blades, heat treated chipper steel with chrome content. 3.125" x .25"

6. ADJUSTABLE, 4-WAY ANVIL

- To ensure good quality chipping ability.
- Chipping blade edge angle is 45 degrees for pulling logs and limbs into the chipper.

7. EASY ACCESS

• The disc is accessible through the hinged disc cover by removing one bolt, which exposes one-half of the disc for easy access to the chipping blades and for easy inspection and maintenance.

8. 360° ROTATING DISCHARGE CHUTE WITH DEFLECTOR CAP

• Put the chips where you want them the first time.

HEAVY-DUTY CONSTRUCTION

Heavy .25" [6.35mm] steel throughout, seam welded.

10. LARGE FEED HOPPER

• Feed your prunings or limbs into a 27" x 28" [68.6cm x 71.1cm] opening.

11. CHIPPER CHUTE

Opening is 5.5" x 7" [14cm x 17.8cm] (for side limbs).

12. ADJUSTABLE JACK STAND (73413 & CH4614 (73420) TOW-ABLE MODELS)

• Allows one person to easily maneuver the chipper and hook up to a vehicle.

13. TORSION AXLE SUSPENSION (CH4614 (73420) TOWABLE MODEL)

• A towable torflex suspension axle with 5.30 x 12 [13.5cm x 30.5cm] tires.

14. WEIGHT

- 614cc Honda chipper weighs 820 lbs. [372kg]
- PTO chipper weighs 600 lbs. [272kg]

15. 2" [5.08CM] BALL COUPLER

16. SAFETY

Meets all applicable ANSI safety standards.

17. PARTS

- Single-Edge Chipper Blade Kit (#70453)
- Double-Edge Chipper Blade Kit (#72493)



Find a dealer near you!

Call us at 800.247.7335 or Log onto www.BearCatProducts.com

> P.O. Box 849, West Fargo, ND 58078 Email: sales@BearCatProducts.com Fax: 701.282.9522

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com