



# FlexScan® L771

49.7 cm (19.6 inch) Class Color LCD Monitor

The FlexScan L771 is the first flat panel display to offer the screen size and high resolution capability of 21" CRT monitors while giving users precise control over color parameters. Not only is this product ideal for traditional LCD monitor domains such as dealing rooms and stock bourses, but its specifications and overall performance give DTP and CAD professionals a long awaited flat panel alternative.

## Features:

- 19.6" TFT panel with 1600 × 1200 native resolution.
- 150° horizontal and vertical viewing angles.
- 0.249 mm × 0.249 mm fine pixel pitch.
- Arm/wall mounting capability.
- Image scaling and smoothing.
- ColorManagement function for improved color control.
- USB hub with one upstream and four downstream ports.
- Support for Kensington's MicroSaver® security system.
- TCO'99 compliant.
- Attachable sound unit for multimedia applications and video conferencing.
- Cabinet color available in gray or black.



# FlexScan® L771

49.7 cm (19.6 inch) Class Color LCD Monitor



## ColorManagement

Detailed control over color settings is now possible on an LCD monitor with the FlexScan L771's ColorManagement. This function lets the user freely adjust hue, gain, saturation, and color temperature in 500K increments from 4,000K - 10,000K.

## Three Mode Viewing

In addition to a normal mode display, the FlexScan L771 can scale resolutions less than the 1600 × 1200 maximum to enlarged or full screen modes.

## Improved Smoothing

A newly improved smoothing function included with the FlexScan L771 refines horizontal lines and letter width of scaled resolutions to a degree of precision previously unattainable.

## USB Hub

The FlexScan L771 includes a USB hub for the plug and play of USB compliant peripherals. Placement of the hub on the LCD panel assures continued use of the peripherals when the display is mounted on an arm or a wall.

## Energy Efficiency

At only 53 watts, the FlexScan L771 consumes approximately 40% of the power needed by its 21" CRT counterparts. When the off timer function or EIZO's own PowerManager™ is activated, consumption falls to less than 3 watts for further energy savings.

## Compliance with International Standards

The FlexScan L771 meets the requirements of the world's strictest standards for emissions, safety, recycling, and power management including TCO'99, TÜV Rheinland Ergonomie Geprüft, the CE Mark, Energy 2000, and the EPA ENERGY STAR® Program.





## FlexScan® L771 Specifications

Panel Type	49.7 cm (19.6 inch) TFT color LCD panel
Pixel Pitch	0.249 mm × 0.249 mm
Display Color	16.7 million colors
Viewing Angle	Horizontal: 150° Vertical: 150°
Scanning Frequency	H: 27 - 94 kHz, V: 50 - 85 Hz (up to 75 Hz at 1600 × 1200)
Brightness	200 cd/m <sup>2</sup> (typical)
Contrast Ratio	300:1 (typical)
Input Signals	RGB Analog
Input Terminal	D-Sub mini 15 pin × 2
Active Display Size	398 mm (W) × 299 mm (H)
Viewable Image Size	497 mm (diagonal)
Recommended	1600 dots × 1200 lines
Resolution	
Plug & Play <sup>1</sup>	VESA DDC 2B
Screen Control	ScreenManager®, One Touch Auto Adjustment Function
Power Management System	VESA DPMS, EIZO MPMS <sup>2</sup>
Power Consumption	53 watts (typical)
Power Save Mode	Less than 3 watts
Dimensions	472 mm (W) × 478 mm (H) × 218 mm (D) (with base) 472 mm (W) × 399 mm (H) × 93.5 mm (D) (panel only)
Net Weight	9.5 kg (with base) 7.7 kg (panel only)
Safety Standards	TÜV Rheinland/GS, CB, CE Mark
Ergonomic/Environmental Standards	TÜV Rheinland/Ergonomie Geprüft (including ISO 9241-3,-7,-8, and MPR-II), EPA ENERGY STAR® Program, Energy 2000, TCO'99 <sup>3</sup>
USB Standard	USB Standard Rev. 1.1
USB Ports	1 upstream port (for computer or another hub) 4 downstream ports (for peripherals)

<sup>1</sup>Only Valid when computer system supports all Plug & Play functions (personal computer, graphics board, Windows® 95/98/2000). For more details, please refer to the Windows 95/98/2000, personal computer, and graphics board manuals or contact the manufacturers.

<sup>2</sup>EIZO MPMS is a power management system developed by EIZO to replace NUTEK which was discontinued at the end of 1997.

<sup>3</sup>Black cabinets are not TCO'99 compliant.



## i-Sound™ Sound Unit

Attachable sound unit with full range bass reflex and amplifier output of two watts per channel. Cabinet color is available in gray or black.



**EIZO NANO CORPORATION**

153 Shimokashiwano, Matto, Ishikawa 924-8566

Japan

Phone: +81 76 277-6792 Fax: +81 76 277-6793

http://www.eizo.co.jp/

Specifications are subject to change without notice.

ENERGY STAR® is a U.S. registered mark. As an ENERGY STAR® Partner, Eizo Nanao Corporation has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. Copyright © 2000 Eizo Nanao Corporation. All rights reserved. All product names are trademarks or registered trademarks of their respective companies. PowerManager and i-Sound are trademarks, and FlexScan, EIZO, and ScreenManager are registered trademarks of Eizo Nanao Corporation.

Download from [www.Somanuals.com](http://www.Somanuals.com). All Manuals Search And Download.

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>