

## DEFY ADVANCED 3

Introducing the all-new Defy Advanced. Lighter, stiffer, more aggressive high-performance, from the composite technology leader. Aero speed meets the road-smoothing ride of a perfectly engineered composite structure. It's go-fast versatility, for the club ride or race day.



## SPECIFICATIONS

FRAME	SIZES	XS,S,M,M/L,L,XL
	COLORS	Team Blue/Silver/Composite
	FRAME	Advanced-Grade Composite
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Alloy Anatomic Bend 31.8
	STEM	Giant Alloy 4-bolt
	SEATPOST	Vector Composite Seatpost
	SADDLE	Giant Performance
	PEDALS	Crank Brothers Smarty
DRIVETRAIN	SHIFTERS	Shimano 105
	FRONT DERAILLEUR	Shimano 105
	REAR DERAILLEUR	Shimano Ultegra
	BRAKES	Tektro R530 Dual Pivot
	BRAKE LEVERS	Shimano 105
	CASSETTE	Shimano 105 12/27, 10-speed
	CHAIN	Shimano 105
WHEELS	CRANKSET DOUBLE	FSA Gossamer MegaExo, 34/50
	CRANKSET TRIPLE	FSA Gossamer MegaExo, 30/39/50
	BOTTOM BRACKET	Shimano Dura-Ace, Internal Press Fit
	RIMS	Mavic CXP22
	HUBS	Formula sealed Cartridge Bearing 24/28h
SPOKES	SAPIM Race, 14/15g	
TIRES	Michelin Speedium 2, 700x25 Folding	
EXTRAS		

## FRAME TECHNOLOGY

Advanced-grade composite ensures precise frame alignment and structural perfection, with aero sculpted main tubes and a new Vector aero seatpost to give you every edge on those solo efforts. Ride-tuned composite layout and endurance position geometry let you ride longer and stronger than ever before.



## FEATURES

- 10-speed Shimano 105 shifting with Ultegra rear derailleur
- Crank Brothers Smarty pedals
- Mavic CXP22 rims, Formula sealed hubs/SAPIM race spokes, wheelset
- Available in both compact double and triple drivetrains

## FRAME GEOMETRY

Actual Frame Size	Part Number	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters	Double	Triple	degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	384542	384642	71.0	74.0	51.5	12.5	42.0	98.3	29.0
S/46.5 cm	384543	384643	72.0	74.0	53.0	14.5	42.0	99.0	29.8
M/50.0 cm	384544	384644	72.5	73.0	54.5	16.5	42.0	99.0	30.7
M/L/53.5 cm	384545	384645	72.5	73.0	56.0	18.5	42.0	100.5	31.2
L/55.5 cm	384546	384646	72.5	72.0	57.5	20.5	42.0	100.8	31.9
XL/58.5 cm	384547	384647	72.5	72.0	59.5	22.5	42.0	102.8	32.7

\*Seat angle is actual

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

Specifications and availability subject to change without notice.

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>