

# TCR ADVANCED SL 2

All new. All race. All conquering. That's the TCR Advanced SL. Developed for the pro ranks, tested in the world's toughest races from the Spring Classics to the Tour de France and the choice of High Road's Team Columbia. Ready to ride. Ready to rip. Ready to win.



## SPECIFICATIONS

FRAME	SIZES	XS,S,M/L,L,XL
	COLORS	Composite/Charcoal
	FRAME	Advanced SL-Grade Composite
	FORK	Advanced SL-Grade Composite, Full Composite OverDrive Steerer
COMPONENTS	SHOCK	N / A
	HANDLEBAR	Race Face Revolution, 31.8
	STEM	Race Face Revolution
	SEATPOST	Giant Vector Composite Seatpost
	SADDLE	Fi'zi:k Arione w/ k:i:um rails
	PEDALS	Not Included
	DRIVETRAIN	SHIFTERS
FRONT DERAILLEUR		Shimano Ultegra
REAR DERAILLEUR		Shimano Ultegra
BRAKES		Shimano Ultegra
BRAKE LEVERS		Shimano Ultegra
CASSETTE		Shimano Ultegra 12/25, 10-speed
CHAIN		Shimano Ultegra
CRANKSET		Shimano Ultegra, 39/53
WHEELS	BOTTOM BRACKET	Shimano Dura-Ace, Internal Press Fit
	RIMS	Mavic Ksyrium Elite
	HUBS	Mavic Ksyrium Elite
	SPOKES	Mavic Ksyrium Elite
	TIRES	Michelin Pro Race3, 700x23
	EXTRAS	

## FRAME TECHNOLOGY

Giant's lightest, stiffest, fastest road racer ever. Handcrafted, engineered precision creates the new benchmark for pedaling stiffness and efficiency. From its sleek seatpost to the massive MegaDrive rectangular downtube and oversized toptube, this is pure Advanced SL-grade composite performance. Without compromise.



## FEATURES

- Full Shimano Ultegra component group
- Race Face Revolution handlebar and stem, Giant Vector seatpost
- Mavic Ksyrium Elite wheelset

## FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	386642	71.0	74.5	52.0	12.0	40.5	97.7	28.5
S/46.5 cm	386643	72.0	73.5	53.5	13.5	40.5	97.4	29.2
M/50.0 cm	386644	73.0	73.0	55.5	15.0	40.5	98.0	30.1
M/L/53.5 cm	386645	73.0	72.0	57.0	17.0	40.5	98.6	31.0
L/55.5 cm	386646	73.0	72.0	58.5	18.5	40.5	100.1	31.7
XL/58.5 cm	386647	73.0	72.0	60.5	20.0	40.5	102.1	32.4

\*Seat angle is actual

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

Specifications and availability subject to change without notice.

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>