

TCR ALLIANCE 0

The TCR Alliance is a distance runner with sprinters' legs, combining aluminum's incredible stiffness-to-weight ratio and composite's unbeatable tunability for a plush, supple ride with amazing power transfer. Go the distance with speed, and in comfort.



SPECIFICATIONS

FRAME	SIZES	XS,S,M,M/L,L,XL
	COLORS	Team Blue/Composite
	FRAME	Alliance Composite/Aluminum Technology
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Race Face Cadence, 31.8
	STEM	Race Face Cadence
	SEATPOST	Giant Composite, 27.2
	SADDLE	Fi'zi:k Aliante Sport w/ Manganese rails
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	Shimano 105
	FRONT DERAILLEUR	Shimano 105
	REAR DERAILLEUR	Shimano Ultegra
	BRAKES	Shimano 105
	BRAKE LEVERS	Shimano 105
	CASSETTE	Shimano 105 12/25, 10-speed
	CHAIN	Shimano 105
	CRANKSET	Shimano 105, 39/53
	BOTTOM BRACKET	Shimano, External
WHEELS	RIMS	Mavic Aksium
	HUBS	Mavic Aksium
	SPOKES	Mavic Aksium
	TIRES	Michelin Lithion, 700x23 Folding
	EXTRAS	

FRAME TECHNOLOGY

Composite main tubes and an aluminum sub-structure make the TCR Alliance supple yet stiff, perfect for sprint finishes and fast centuries. Whether you live for the weekend crit or that epic ride, the TCR Alliance will see you through. Quickly.



KEY UPGRADES (FROM TCR ALLIANCE 1)

- Full 10-speed Shimano 105 groupset with Ultegra rear derailleur
- Lightweight Race Face Cadence handlebar and stem, Fi'zi:k Aliante Sport saddle
- Lighter, more aerodynamic Mavic Aksium wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	385442	71.0	74.5	52.0	12.0	40.5	97.7	28.4
S/46.5 cm	385443	72.0	73.5	53.5	13.5	40.5	97.4	29.2
M/50.0 cm	385444	73.0	73.0	55.5	15.0	40.5	98.0	30.1
M/L/53.5 cm	385445	73.0	72.5	57.0	17.0	40.5	99.2	31.1
L/55.5 cm	385446	73.0	72.5	58.5	18.5	40.5	100.6	31.6
XL/58.5 cm	385447	73.0	72.0	60.5	20.0	40.5	102.1	32.3

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

Specifications and availability subject to change without notice.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>