ERICSSON W30/35

Fixed Wireless Terminal for WCDMA/HSDPA Networks Business Applications

For W2X/W3X Fixed Wireless Terminals





The Ericsson W30/35 Mobile Broadband Router utilises an existing 2G/EDGE or 3G/HSPA mobile network to provide phone, broadband and fax services to enterprise and small businesses, without the need for a fixed telephone line or access to a cable network. Simply insert a SIM card into the Mobile Broadband Router, plug it into a power point and the device is ready for use.

With the W30, a user can connect multiple computers via the Ethernet ports or in-built WLAN and a printer/USB key/external hard drive to the USB slot for sharing to all connected users. In addition to these features, the W35 also provides telephone and fax functionality. The W30/W35 offers unlimited application possibilities for businesses that require staff mobility, some examples include:

Office in a Box: provides an office solution to sectors such as mining, construction and emergency services where fixed infrastructure is costly and time prohibitive;

Data backup & redundancy: ensure business continuity to retail, banking and emergency services by providing a wireless voice and data redundancy path to guard against fixed line outages;

Fixed Line alternative: a cost and time efficient solution for broadband and fixed phone services, where POTS infrastructure is unavailable;

Mobile Workforce: event management, consulting and auditing sectors can bring their own wireless branch office (VPN) to a temporary work location.



Feature Summary:

- Out of the box, plug and play device
- Simultaneous use of broadband, voice and fax services (W35 only)
- High quality voice and fax services are provided via a telephony interface. A broad range of network related services such as Prepaid Subscription, Calling Line Identification, Call Waiting, Call Forwarding, Call Return and Multiparty Conference Calls are available (W35 only)
- Multi device data networking via both wired and wireless interfaces:
 - Four switched Ethernet 10/100BaseT ports for wired LAN connectivity, with rate auto-negotiation and MDI/MDIX auto-detection support
 - An integrated WLAN 802.11 b/g (data rates up to 11/54Mbps) access point for wireless LAN connectivity
 - One USB port (USB 2.0 Host Controller) for file and printer sharing
- Dual software image feature to ensure reliability of the device during software updates
- Flexible networking capabilities:
 - Comprehensive set of networking and IP protocols such as bridging, routing, DNS, DHCP server/relay, SNTP, and NAT

- L2TP tunnelling providing a mechanism for tunnelling Ethernet frames between two peers over an existing network
- VPN pass-through supporting VPN protocols for standard IPSec VPN applications
- IPsec/VPN termination supporting one IPsec/ VPN tunnel using Site-to-Site configuration
- Stateful packet filtering firewall (using Linux Kernel iptables)
- Wireless security features including standard WLAN WEP, WPA and WPA2 encryptions and MAC Association Control
- QoS feature for outgoing IP traffic via the WAN interface
- Local and remote administration and management with SSH (Secure Shell) support. Web-based user interface for configuration of the device with wizard support
- SIM-lock and PIN-lock functions prevent unauthorized use of the subscription, while a mechanical antitheft kit is available to physically secure the Ericsson W25 to the wall
- Supports over the air remote software image installation, shell script execution and configuration changes.

Technical Specification:

Dimensions	H105 x W210 X D35mm
M/a i what	, , , , , , , , , , , , , , , , , , ,
Weight	350g
Frequency Bands	WCDMA/HSPA 850/1900/2100MHz GSM/GPRS/EDGE 850/900/1800/1900 MHz
Data Rate	Downlink: up to 7.2Mbps Uplink Up to 2.0Mbps (W30) 5.76Mbps (W35)
Power	Power Adapter input: 100 - 240 VAC, 50-60Hz Power Adapter output: 12VDC Unit Power input: 10 - 28 VDC Power consumption: Up to 15W
Environmental Specification	Operating Temp: 0°C to +50°C Operating Temp Battery: 0°C to +40°C Storage Temp: -45°C to +85°C Operating Rel Humidity: 5 - 95% Storage Humidity: 10 - 100%
External Interfaces	Qty 4 x Ethernet RJ45 Qty 1 x USB 2.0 Qty 1 x Phone Port RJ11 Qty 1 x Fax Port RJ11 Standard SIM/USIM slot
In the box:	MBR Unit AC/DC Power Supply (AU/EU/US/UK) Ethernet Cable (3.0m) CD with User Guide Quick Installation Guide
Optional Accessories	Window mounted antenna Roof Mounted antenna Surge Protector USB Cable Backup battery (voice operation only)

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com