Foodservice System Housing for Dro	DEV9100-20 CGS-20 20" Sing	jle Housing
	CGS-20 20" Single Housing: DEV9100-20	BENEFITS 20" low profile Slim Line single bowl housing Manufactured of durable polypropylene and has excellent chemical resistance System includes water pressure gauge Equipped with a pressure relief button to relieve water pressure during cartridge changes Includes wall mounting bracket and hardware for fast and easy installation System is shipped fully assembled Choose the appropriate cartridge for your needs Cartridge sold separately
INSTALLATION TIPS Choose a mounting location suitable to support the full weight of the system when operating Install vertically so bowl hangs down Allow 2-1/2" clearance below the cartridge for easy cartridge replacement Make sure O- ring on bowl is sufficiently lubricated Always screw on bowls by hand; do not use a housing wrench Flush filter by running water through filter according to cartridge instructions	OPERATION TIPS Change cartridges on a regular 6 month preventative maintenance program Change cartridges when capacity is reached or when pressure decreases Always inspect O-ring; change and/or lubricate if necessary Clean bowl with mild solution of detergent before inserting new cartridge Always flush the filter cartridge at time of installation and cartridge change	APPLICATION/SIZING For foodservice applications Bowl housing assembly accepts drop in cartridges Capacity: varies according to filter cartridge used

CGS-20 20" Single Housing

SPECIFICATIONS

Overall Dimensions: 25"H x 9.25"W x 5.25"D

Inlet connection: 3/8"

Outlet connection: 3/8"

Service Flow Rate: Maximum 2.0 gpm (7.6 Lpm)

Pressure Requirements: 30 - 125 psi (2.1 – 8.6 bar), non-shock

Temperature: 40 - 100°F (4.4 - 38°C)

No electrical connection required

The contaminants or other substances removed by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

9.25' $\left(\mathbf{\mathcal{G}}\right)$ WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



System Tested and Certified by NSF International against NSF/ANSI Standard 42 for the reduction of:

Standard No. 42: Aesthetic Effects Chemical Unit Taste and Odor Reduction Chlorine Reduction

NOTE: NSF Listings vary according to cartridges used in housing.



Worldwide Headquarters: EVERPURE, LLC 1040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323-7873 Tel (630) 307-3000 Fax (630) 307-3030 http://www.everpure.com

In Europe: Pentair Water Belgium B.V./B.A. Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals BELGIUM TEL: +32.(0).14.283.500 FAX: +32.(0).14.283.505

In Iapan: Hashimoto MN Bldg. 7F 3-25-1 Hashimoto Sagamihara-Shi Kanagawa 229-1103 JAPAN TEL: 81.(0)42.775.3011 FAX: 81.(0)42.775.3015

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com