	08.09	C · · · ·
fotal Water Treatment System for S	eam Applications	
	SC10-21 System: EV9797-83 CG5-20 Carbon Block Cartridge: DEV9108-25 SS-10 Scalestick Cartridge: EV9799-02	BENEFITS
		Total system delivering high quality filtered wat with scale inhibition capabilities
		Improves performance, maximizes energy efficiency and increases the life of steam equipment
		Reduces chlorine-induced corrosion
		Drop- in style filter bowl housings 5- micron block cartridge for particulate and
		chlorine reduction
		Long lasting SS-10 cartridge for scale control Outlet pressure gauge pre-assembled onto head
NSTALLATION TIPS	OPERATION TIPS	A P P L I C A T I O N / S I Z I N G
Choose a mounting location suitable to support he full weight of the system when operating	Replace CG5-20 Carbon Block cartridge whenever its capacity is reached (12,000 gal.) or when it becomes excessively dirty (observed visually or by flow restriction) Change SS-10 Scalestick Cartridge before HydroblendTM Compound is completely used up	For commercial steam applications For use with foodservice steamer and combi-over applications
Jse minimum 1/2" O.D. Tubing, or equivalent,		
rom the outlet of the filtration unit to the teamer/combi- oven		
teamer/ combr- oven		
Jse the water form the SC Series unit only on		
Jse the water form the SC Series unit only on teamer/combi-oven feed and make-up water.	Always flush filter cartridge at time of installation and cartridge change	
Jse the water form the SC Series unit only on teamer/combi- oven feed and make- up water. Do not use to treat condensate cooling water install vertically with cartridges hanging down	Always flush filter cartridge at time of installation and cartridge change	

S P E C I F I C A T I O N S

Overall Dimensions: 25.75" H x 9.75" W x 5.25" D

Inlet connection: 1/2" FNPT

Outlet connection: 1/2" FNPT

Service Flow Rate: Maximum 6 gpm

Pressure: 10-125psi (0.7-8.6 Bar), non shock

Temperature: 35-100°f (2-38°c)


Shipping Weight: 10lbs.


Operating Weight: 15lbs.

The contaminants or other substances removed or reduced by this system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality with out adequate disinfection before or after the system.

Scalestick is NSF Certified under NSF/ANSI Standard 42 for materials

SC10-21 Steam Filtration System





WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



Worldwide Headquarters: EVERPURE, LLC 1040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323-7873 Tel (630) 307-3000 Fax (630) 307-3030 http://www.everpure.com In Europe: Pentair Water Belgium B.V./B.A. Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals BELGIUM TEL: +32.(0).14.283,500 FAX: +32.(0).14.283,505 In Japan: Hashimoto MN Bldg, 7F 3-25-1 Hashimoto Sagamihara-Shi Kanagawa 229-1103 JAPAN TEL: 81.(0)42.775.301 FAX: 81.(0)42.775.3015

Everpure 1040 Muirfield Drive Hanover Park, IL 60133 Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com