

# MR-20 Replacement Cartridge

# Mineral Reduction Cartridge



MR-20 Replacement Cartridge: EV9273-69

EV9273-69

#### BENEFITS

Improves equipment life and performance by removing at least 90%+ of all dissolved solids using Reverse Osmosis Separation Technology

Especially useful on low capacity steamers, warmers, small steam boilers and other evaporative equipment that are not emptied each day

Heating surfaces maintain peak heat transfer efficiency, reducing cycle times and energy consumption

Limits limescale build-up, which can cause excessive machine downtime and maintenance costs

Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination

### INSTALLATION TIPS

Install vertically with cartridge hanging down

Allow 2-I/2" clearance below the cartridge for easy cartridge replacement

Use piping materials suitable for high-purity water after MRS System

Refer to Installation, Operation & Maintenance Manual for cartridge flushing and RO start-up

#### OPERATION TIPS

Change MR Cartridge on a regular 24 month preventative maintenance program

Change MR Cartridge when output capacity diminishes by 15%, or when output pressure becomes too low.

Always flush the MR cartridge at time of installation and cartridge change

Proper pre-treatment is required to control MR Cartridge (membrane) scale formation and/or

- Raw water hardness in excess of 7 grains per gallon should be softened to extend cartridge life

- The raw water may contain particulates and the use of a pre-filter is recommended

Contact EVERPURE Technical Service for pre-treatment recommendations

#### APPLICATION/SIZING

Mineral Reduction Cartridge for High TDS Waters

Capacity: 21 Gallons per Day nominal

Ideal for:

Flash steamers, conventional steamers, cheese melters, combi-ovens and coffee/espresso machines

# SPECIFICATIONS

Overall Dimensions: 14.5"H x 3.25"D

**Daily Production Rate:** 

21 GPD (79.5 lpd) Nominal. Water pressure, feedwater quality and temperature will effect actual daily production rate

Service Flow Rate:

Dependent on water volume and pressure in storage tank(s), and line size(s) to equipment

**Pressure Requirements:** 

40 - 100 psi (276-689 kPa), non-shock.

Inlet Temperature:


35 - 100°F (2-38°C)

Inlet TDS:

1,500 ppm max recommended

The contaminants or other substances removed or reduced by this system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

# MR-20 Replacement Cartridge



## WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



Worldwide Headquarters: EVERPURE, LLC 1040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323-7873 Tel (630) 307-3000 Fax (630) 307-3030 http://www.everpure.com In Europe:
Pentair Water Belgium B.V./B.A.
Industriepark Wolfstee
Toekomstlaan 30
B-2200 Herentals
BELGIUM
TEL: +32.(0).14.283.500

TEL: +32.(0).14.283.500 FAX: +32.(0).14.283.505 In Japan:
Hashimoto MN Bldg. 7F
3-25-1 Hashimoto Sagamihara-Shi Kanagawa 229-1103 JAPAN
TEL: 81.(0)42.775.3011
FAX: 81.(0)42.775.3015 Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com