EV9318-60 Exubera Water Appliance

Exubera: EV9318-60



BENEFITS

Produces ambient, chilled and chilled carbonated water

Combined with Everpure filtration technologies, allows for premium carafe water

Capable of supplying water-cooled to 40°F

Efficient ice bank technology

Consumes only 350 watts of electricity when compressor is cycling

Can be plumbed to coffee or ice machine

Durable construction

UL Approved

INSTALLATION TIPS

OPERATION TIPS

Position the appliance in the point of installation, away from sources of heat and direct sunlight

Do not install the appliance outdoors and in very damp rooms

The appliance should be positioned in such a way as to leave approximately 2.40 to 2.80 inches of space free for air to circulate freely

Fill the ice bank before connecting CO2, main water supply or power

Requires CO2 cylinder to provide carbonation $(\mathrm{EV}_{9318}\text{-}62)$

Before connecting CO2, run water through dispenser

Flush all dispensers before use

Ensure John Guest fittings are secure before operation

To ansure the highest quality water, use in

To ensure the highest quality water, use in combination with an Everpure filtration system

Before making the water connection, make sure the incoming water pressure is between 14.5 psi and 43.5 psi

If the incoming water pressure is below 14.5 psi or the flow rate is less than 0.50 gpm, fit a device capable of increasing the pressure (such as an autoclave or similar)

The pressure is especially important for those water coolers fitted with a carbonation device

If the incoming water pressure exceeds 43.5 psi, predispose a pressure reducer capable of reducing the latter to the 14.5 psi and 43.5 psi

Advice on using the appliance for carbonated water: To guarantee the correct operation of the pump in time, the appliance must always be operated with water in the cooling circuit A P P L I C A T I O N / S I Z I N G

Maximum Cold Water Capacity: 6.6 gph

Suggested tubing: 3/8" OD, 1/4" ID polyethylene tubing

Exubera Water Appliance

S P E C I F I C A T I O N S

Overall dimensions: 16"H x 10"W x 18"D

Inlet & Outlet connections: 1/4" O.D. for inlet and 6 mm O.D. tubes for outlets

Power Supply: 115 VAC @ 60 Hz, 350 W

Compressor Power: 1/12 HP

Refrigerant Gas: CFC Free R134a

Maximum Cold Water Capacity: 6.6 gph

Water Pressure Range: 14.5 - 43.5 PSI (2 – 3 Bars)

0 0 6 16" 18' Need UL Logo here WARRANTY Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request. =V=ZPIR= Worldwide Headquarters: In Europe: In Japan: Pentair Water Belgium B.V./B.A. EVERPURE, LLC Hashimoto MN Bldg. 7F 1040 Muirfield Drive Industriepark Wolfstee 3-25-1 Hashimoto Sagamihara-Shi Hanover Park, Illinois 60133 Toekomstlaan 30 Kanagawa 229-1103 B-2200 Herentals JAPAN Toll Free (800) 323-7873 BELGIUM Tel (630) 307-3000 TEL: 81.(0)42.775.3011

TEL: +32.(0).14.283.500

FAX: +32.(0).14.283.505

FAX: 81.(0)42.775.3015

Everpure 1040 Muirfield Drive Hanover Park, IL 60133

Fax (630) 307-3030

http://www.everpure.com

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com