

Specifications — SPA 12 AAP Architectural Speaker

Audio/acoustic and electrical

Speaker type	1-way, full range architectural speaker
Frequency range	350 Hz to 15 kHz, -10 dB, half space
Power capacity	5 W continuous pink noise 10 W continuous program
Nominal sensitivity	86 dB SPL, 1 W (2.83 V) @ 1 m, half space
Nominal impedance	8 ohms
Nominal coverage	150° conical coverage
Driver	2.5" (64 mm) full-range
Input connector	1 solder terminal, 2 pin

General

Package	1 speaker
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Mounting	Mountable into the four space AAP opening of an Extron Cable Cubby (models 300C, 300S, 600, 800); an HSA 400 or HSA 402; or a mounting frame (AAP 102, AAP 102 FSR, AAP 106 AKM UK, AAP 104, AAP 202)
Enclosure type	Metal faceplate with plastic rear enclosure
Enclosure	
Faceplate	2.8" H x 3.5" W x 0.1" D (71 mm H x 89 mm W x 3 mm D) (four space AAP plate)
Device	2.8" H x 3.5" W x 2.5" D (71 mm H x 89 mm W x 64 mm D)
Product weight.....	0.5 lbs (0.3 kg)
Shipping weight.....	3 lbs (2 kg)
Warranty	5 years parts and labor

NOTE All nominal levels are at ±10%.

NOTE Specifications are subject to change without notice.

(7.51-011206-D5)

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>