

Specifications — SRI 200 Scan Rate Indicator

Video input

Horizontal frequency 10 kHz to 150 kHz
Vertical frequency 30 Hz to 200 Hz

General

Power 3VDC supplied by 2 internal lithium batteries (Panasonic BR2325 or equivalent), auto power
Temperature/humidity Storage -40° to +158°F (-40° to +70°C) / 10% to 90%, non-condensing
Operating +32° to +122°F (0° to +50°C) / 10% to 90%, non-condensing
Rack mount No
Enclosure type Plastic
Enclosure dimensions 1.0" H x 2.2" W x 3.5" D
2.5 cm H x 5.6 cm W x 8.9 cm D
Product weight 0.2 lbs (0.1 kg)
Shipping weight 1 lbs (0.5 kg)
Vibration ISTA/NSTA 1A in carton (International Safe Transit Association)
Listings UL, CUL
Compliances CE, FCC Class A
MTBF 30,000 hours
Warranty 3 years parts and labor

NOTE *Specifications are subject to change without notice.*

(7.40-111401_010603-D1+)

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>