


Specifications – MHRHF-5 Cable

Description Part No. (length) Model	UL NEC/ C(UL) CEC UL AWM Temp.	No. of Cond.	Standard Lengths		Shipping Weights		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials (% coverage) Nom. DCR	Nominal OD		Nom. Imp. of Prop. (ohms)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/ft	pF/m	MHz	dB/100 ft	dB/100 m
(5) 26 AWG MiniatureCoax • Aluminum Foil (100%) + Tinned Copper Serve Shield																			
Nonplenum Cable • Gas-injected Foamed Polyolefin Insulation • Halogen-Free Polyolefin Inner Jackets • Orange Halogen-Free Polyolefin Outer Jacket																			
22-126-02 (150 m) 22-126-03 (300 m) MHRHF-5  Min. bend radius: 4.0"	NEC CM LSFOH IEC 322-3 75 °C	5 coax	492.1	150	27	12.2	26 AWG (7/34) 0.019" 0.48 mm, Tinned Cu 41 ohms/ 1k ft, 135 ohms 1 km	0.076	1.93	Alum. Foil (100%) Tinned Cu Braid (95%) 12.2 ohms/ 1k ft, 40.0 ohms/ 1 km	Single: 0.105 2.67 red, green, blue, black, yellow		75	81%	16.7	54.8	1	-0.5	-1.7
			984.3	300	71	32.2		Overall: 0.360 9.14 orange			5	-1.2			-3.9				
								10	-1.7		-5.5								
								20	-2.4		-7.8								
								50	-3.8		-12.3								
								71	-4.5		-14.8								
								100	-5.4		-17.6								
								135	-6.3		-20.6								
								180	-7.3		-23.9								
								200	-7.7		-25.4								
				270	-9.1	-29.9													
				400	-11.5	-37.3													
				750	-16.4	-53.8													
				1000	-19.5	-64.0													
				3000	-43.6	-143.0													

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>