

INSTALLING BATTERIES

The MA003 Amplifier operates with two 9-volt alkaline batteries. Two battery compartments can be found on the back of the amp, on either side of the speaker.

Replace both batteries by following these steps:

Open the battery compartment door, pinch the tab, and pull the door to open.

To install a new battery, snap the +/- terminals of the battery into place on the connector pad.

Place the attached battery into the compartment.


Close the compartment door.

Do not mix old and new batteries. Do not mix alkaline standard (carbon-zinc) and rechargeable (nickel-cadmium) batteries.



CENTION - ELECTRICELLY OPERATED PRODUCT Not recommended for children under 8 years of age. As with all electric products, precautions should be observed during handling and use to prevent electric shock.

NOTE TO PARENTS: If you purchase an adaptor for this amplifier, it should be periodically examined for conditions that may result in the risk of fire, electric and proce, or injury. If such conditions are found, the adaptor should not be used until property repaired or replaced.



IMPORTANT SAFETY INSTRUCTIONS

Please read carefully before operating your amplifier: Follow these basic precautionary measures to ensure a longer life for your amplifier, and to reduce the risk of electric shock.

1. This unit should be protected from contact with water, moisture, or liquids of any kind.

- 2. This amplifier should only be serviced by a qualified repair technician.
- 3. This unit should not be placed near a heat source (permissible operating temperature range 32–104°F).
- 4. Do not set heavy objects on the power cable or allow the cable to be torn. If the cable needs repair, do not plug the amplifier in. Have the amplifier repaired immediately by a qualified service technician.
- 5. Unplug your amplifier when not in use for extended periods of time.
- 6. Turn amplifier power off when not in use.
- The outside of the amplifier may be cleaned with a dry cloth only. Do not use water or chemicals to clean.
- 8. This unit contains digital circuitry and may cause interference if placed too close to radio or television receivers.


- 9. Do not operate the amplifier if:
 - » the unit or main cable has been visibly damaged
 - » the unit has been dropped
 - » the unit has been exposed to moisture/liquids of any kind » the unit is not functioning properly

Note: If you suspect that your amp is defective, have it checked and repaired by a qualified service technician.

- 10. Do not expose the unit to:
 - » Direct sunlight
 - » Excessive humidity
 - » Excessive dust
 - » Strong vibration
- 11. This unit must be properly grounded.
- 12. To prevent electric shock hazard, do not open the cabinet or chassis of the amplifier.

First Act and the First Act logo are

trademarks of First Act Inc.



© 2008 First Act Inc. All rights reserved.

Download from WWW.Softanuais.com. Al-Manuais Search And Download.

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com