Data Sheet · CONNECT2AIR WLAN · Issue October 2002

CONNECT2AIR WLAN AP-500RP AccessPoint

Low cost / high performance AccessPoint



The CONNECT2AIR AP-500RP AccessPoint is a cost-effective, fully featured wireless router that extends the range of wired Ethernet networks. The CONNECT2AIR AP-500RP delivers the freedom to expand and work more efficiently.

High Performance AccessPoint

The high performance CONNECT2AIR AP-500RP extends the range of your cabled Ethernet network and provides easy network access to mobile users. Difficult to wire locations are now easy accessible. Network management through the Web interface combined with SNMP makes it easy to embed the AP-500RP in a small office or home environment.

Multifunctional and with many features

The CONNECT2AIR WLAN AP-500RP is a multi-functional Broadband Wireless SOHO Router. It provides excellent all-in-one networking solutions to surf the Internet and share the office resources. Its efficiency boosting features will increase effectiveness and save cost in any working environment. It includes the following functions:

- High speed wireless LAN connection:
 11Mbit/s data rate by incorporating Direct Sequence Spread Spectrum (DSSS)
- IEEE 802.11b compatible: allowing interoperability among multiple vendors
- 64-bit or 128-bit WEP encryption
- 10BaseT WAN interface: to connect to DSL or Cable modem for broadband Internet access
- 2 port Fast Ethernet switch: 10/100 Mbit/s auto-sensing
- Parallel printer port: embedded printer server to allow all of the connected Devices (wireless or wired) to share a single printer

- Asynchronous RS-232 serial port: to connect an Analog or ISDN modem for Internet access
- Built-in NAT function: allow multiple PCs and devices to share one Internet connection
- VPN support: PPTP/IPSec pass-through
- Built-in firewall to protect your Intranet
- Browser-based interface for configuration and management:
 OS independent, easy-to-use for quick installation and management of your device
- Multi language support:
 Web Interface supports German, English,
 French, Italian and Spanish

Data Sheel

www.fujitsu-siemens.com



Standard features

- Conform to IEEE 802.11 and IEEE 802.11b
- 64 / 128-bit key RC4 encryption
- MAC Address Control
- Web-based management
- Powerful performance for the most demanding network applications such as Radio Streaming
- Enhanced roaming across disparate locations and infrastructures
- Integrated DHCP Server
- Supported ISP connection types: PPPoE, PPTP, Dial-up via Analog/ISDN modem, fix or dynamic IP

Interfaces

- One RJ-45 port for 10Mbit/s Ethernet WAN connection
- Auto-sensing 2-port switch for 10/100Mbit/s Ethernet LAN connection
- One serial port for PSTN/ISDN dial-up connection and console configuration
- One DB-25 parallel port for printer server
- High speed wireless LAN (IEEE 802.11b DSSS)

Environmental specifications

	Temperature	Humidity		
Operating	0°C to 50°C	95% (non condensing)		
Storage	-10°C to 60°C	95% (non condensing)		

Barometric pressure 740 hPa to 1050 hPa

Hardware specifications

Processor RDC 8822 Memory 512Kbit DRAM

512Kbit Flash

LAN 2 x RJ-45 LAN / 10/100 Mbit/s

auto-sensing

WAN 1 x RJ-45 WAN / 10 Mbps WAN
Printer port 1 x IEEE1284 DB-25 (parallel)
COM port 1 x DB-9 RS-232C (serial)

Radio characteristics

Frequency Range 2412 MHz to 2462 MHz (ISM)
Channel Frequencies 11 freely selectable channels

Antenna System Diversity antenna

Bit Rate 11 Mbit/s, 5.5 Mbit/s, 2 Mbit/s, 1 Mbit/s (Automotic Rate

1 Mbit/s (Automatic Rate

Selection)

Output Power 16 dBm (max.)

Typical Range *	11 Mbit/s	1 Mbit/s
open environment	100 m	300 m
closed environment	35 m	100 m
Receiver sensitivity PER < 8%	-81 dBm	-92 dBm
Typical throughput (excluding headers, etc) using TCP/IP	5 Mbit/s	0.8 Mbit/s

^{*} Above listed throughput and range values are typical characteristics and depend on positioning of the Access Point, Clients and environmental influences and cannot be guaranteed.

Additional features

- Seamless roaming within the 802.11b WLAN infrastructure
- Provide 10Base-T WAN interface to connect with DSL or Cable modem for broadband Internet access
- Asynchronous port for backup routes when the broadband modem fails or is disconnected
- Built-in NAT function: allows multiple PCs and devices to share one Internet connection
- VPN support: PPTP / IPSec pass-through
- Built-in firewall to protect your Intranet
- Access limitation: allow or deny every single wireless device to access the WLAN or LAN
- Browser-based interface for configuration and management: OS independent, easy-to-use for quick installation and management of the device
- Easy to upgrade: using Web, Windows application, or FTP to upgrade new version of firmware
- Built-in printer server: dedicating a personal computer as print server is not needed
- Roaming: AP can be linked via LAN (Distribution system)

Configuration and management

Web-based Utilities

TFTP support

HTTP server for web-based management

Multilanguage support: German, English, French, Italian and Spanish

LED displays

Power Indication

M1 System Status AP-500RP

WAN WAN port activity
WLAN Wireless activity

Link/Act. (1, 2) Link status of corresponding LAN port 10/100 (1, 2) Data Rate of corresponding LAN port

System requirements

PC with 802.11b WLAN Card or network card

Includes

AP-500RP AccessPoint

Power cord

Quick Installation Guide

External Power supply, Input 100/240 V AC, 50/60 Hz

CD with software and documentation

Cat. 5 patch cord

Physical specifications

Dimensions: 220 x 142.5 x 38 mm

Weight: 510 g

Supported Operating Systems

AccessPoint configuration: Win 95, Win 98 (SE), Win ME, Win NT, Win 2000, Win XP, Linux, Macintosh Printer Server SW: Win 95, Win 98 (SE), Win ME,

Win NT, Win 2000, Win XP

Warranty

2 years

Order code

S26391-F2515-L500

Published by Fujitsu Siemens Computers http://www.fujitsu-siemens.ch	All rights, including rights created by patent grant or registration of a utility model or design, are reserved. Delivery subject to availability; right of technical modifications reserved. All hardware and software names used are trade names or trademarks of their respective manufacturers.	Company stamp
	Copyright © Fujitsu Siemens Computers, 11/2002	

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com