



Please read this supplement to the CH270 Manual first.



CH270 Searchlight Sonar



Important Technical Installation Information

.....

The following checklist and information sheets are provided to help you efficiently install your CH270 sonar. If this is a high speed vessel, please pay careful attention to the tube length and fairing instructions.

CH270 Installation Supplement Contents

The following checklist and information sheets are provided to help you properly and efficiently install your CH270 sonar. If this is a high speed vessel, please pay careful attention to the tube length and fairing instructions.

Page

- 1-2 Overall installation checklist - Please return a completed copy to Furuno U.S.A.*
- 3 Fiberglass (FRP) sonar tube installation outline drawing*
- 4-6 High speed hull, sonar tube fairing pictures with comment*
- 7 Tank guide assembly installation and adjustment instructions*
- 8 Motion sensor mounting, location and longer interconnect cables*
- 8 Soundome cover removal and oil installation reminder*
- 9 Checking soundome when in drydock*

Please feel free to contact us with any questions that you may have. Additional information such as this may be found on our web site www.Furuno.com.

This material is provided to augment, not replace, what is found in your CH270 manuals.

CH270 Installation Check Sheet

Vessel Information

Vessel Name: _____
Type: _____ Use: _____
Length: _____ Registry: _____
Operating Speed: _____ Hull Type: _____

CH270 System Information

CH270 Model: _____
Serial Number: _____
Shaft Travel: _____
System Input Voltage: _____

Dealer Information

Dealer Name: _____
Address: _____ City, State, Zip: _____
Installed By: _____
Date: _____ Location: _____

Standard System – MU100C Display Check List

Are all cables and connections tight & strapped? Yes No
Is NMEA data connected and activated? Yes No
What NMEA devices are connected: _____
Has CH252 control head installation & operation been checked? Yes No
Is the unit grounded properly? Yes No

OR

Black Box System – VGA Display Check List

Are all cables and connections tight & strapped? Yes No
Does the monitor display the correct color palette? Yes No
Are the IF8000 dip switches set correctly? Yes No
Is NMEA data connected and activated? Yes No
What NMEA devices are connected: _____
Has CH252 control head installation & operation been checked? Yes No
Is the unit grounded properly? Yes No

CH273 Transceiver Unit Check List

Are all cables and connections tight & strapped? Yes No
Check and note actual input voltage _____
Is the unit grounded properly? Yes No

Motion Sensor or Incinometer Check List

Which sensor is being used, BS704 or MS100? BS704 MS100
Where is the sensor located? _____
Has the sonar been programmed to look for the sensor? Yes No

Sonar Tube Installation Check List

Was a Furuno supplied sonar tube used? Yes No
If not, what was the ID of the sonar tube used? _____
What is the actual length of the sonar tube? _____
Where is the sonar tube mounted? _____
Is the sonar tube on or off the vessels centerline? On Off
Has a sonar tube air venting system been installed? Yes No
Has a forward sonar tube fairing been installed? Yes No

CH270 Installation Check Sheet - continued

CH181 or CH184 Hull Unit Check List

Check and note actual input voltage: _____

- | | | |
|--|------------------------------|-----------------------------|
| Are all cables and connections tight and strapped? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Is the unit grounded properly? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Has the soundome been lowered and raised by hand? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Have the shaft guides been adjusted for 0.5mm tolerance? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Does the shaft have a heading mark inscribed? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Is the soundome 1/2" up, in the sonar tube when retracted? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Has epoxy been used on shaft threads? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Has soundome packing sponge been removed? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Was oil added to the soundome? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |

****CAUTION - Do not lay soundome on its side once oil has been added****

- | | | |
|--|------------------------------|-----------------------------|
| Are all the soundome Phillips Head screws tight? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Have 3 layers of greased cotton packing been used? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Is the safety clamp installed and tightened? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |

Accessories Check List - if applicable

- | | | |
|---|------------------------------|-----------------------------|
| Checked operation of the SC-05WR external speaker? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Checked operation of the CH256 handheld remote control? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |

Sea Trial Check List

Date: _____ Location: _____

Operator: _____

Sea conditions: _____

Maximum detection range for the sea-bottom: _____

Maximum detection range for fish targets: _____

- | | | |
|---|------------------------------|-----------------------------|
| Has the sonar picture been checked for alignment? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Has the auto-retraction feature been checked? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Have the system manuals been given to the operator? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Was any hoist movement noted at maximum speed? | <input type="checkbox"/> Yes | <input type="checkbox"/> No |

Operator Training

Date: _____ Location: _____

Trainer: _____

Training provided for: _____

Necessary Follow-up


Required for: _____

When: _____

Warranty Card Completed and Sent to Furuno USA

Date: _____

Use this drawing for keel installation only.



格納タンクの長さ;
LENGTH OF
RETRACTION TANK;

Lt= mm


**Standard tube length is 1 meter (1000mm).
Minimum tube length is 24 inches (610mm).**

品番 ITEM	品名 NAME	材質 MATERIAL	数量 Q.TY	図番 DWG.NO.	備考 REMARKS
承認 APPROVED	SEP. 6.88 T. NAKAJU	三角法 THIRD ANGLE PROJECTION			
検図 CHECKED	SEP. 6.88 T. NAKAJU	R 度 SCALE			
		1/4			
		名称 TITLE			
		FRP製格納タンク外觀図 FRP RETRACTION TANK OUTLINE DRAWING			

Sonar tube fairings for high speed vessels

Today, many CH270 hull tubes have to be placed in the forward part of the vessel. This location almost guarantees underway turbulence. Although a poor location, space limitations usually make it the only site available for the hull tube and hoist. As the installation manual shows, the best location is always one third to one half way back from the bow. This is okay, because a bit of prior planning and on - site fabrication will allow a very successful installation on a fast, planing hull vessel. When the vessel's bow rises or she is on a plane, you must prevent the hull tube rear wall from becoming a large water scoop. A simple but effective fairing must be constructed. The fairing routes (diverts) the water flow away from the tube opening, preventing it from striking the tube's rear wall. The same principles applicable for bow thruster installations are true for any sonar hull tube.

Properly sized and shaped, the fairing will minimize turbulence and destructive soundome or shaft movement. Some vessels may require several fairing size and shape adjustments to be absolutely successful. Pictures of several typical, successful fairings are attached for your information and use. A carefully fitted installation will insure you many years of reliable, trouble free CH270 sonar operation.







Sonar retraction tank

Bow

Original keel line

— Added fairing —



Please confirm that the narrowest gap between the tank guides and the retraction tube wall is **0.5mm**. Adjust if necessary.

Motion Sensors, Inclinometers and Longer Interconnect Cables

This valuable accessory unit must be mounted correctly to obtain any benefit from it:

- a) Select a mounting location that is dry and vibration free*
- b) The selected location should be as close to the sonar hoist unit as possible*
- c) Mount the unit level (only compensating for normal vessel trim)*
- d) Line the unit up "fore and aft" accurately*
- e) Mount the unit "right side up" only*

If a longer interconnect cable assembly is required, the following options are available:

<u>Part number</u>	<u>Description</u>
MS1-CBL-15M	15 meter signal cable assembly
MS1-CBL-30M	30 meter signal cable assembly
MS1-CBL-50M	50 meter signal cable assembly

Note:

The MS100 compensates for any vessel pitching and rolling at sea. To properly set itself the motion sensor must be powered up while the vessel is in a stable condition. This step is easier to accomplish at the dock. Please get in the habit of powering up the entire CH270 system prior to departing from the dock. This one easy step will ensure proper operation of the MS100 and enhanced CH270 performance for the duration of the voyage.

Soundome Cover Removal and Replacement

To detach or replace the soundome cover assembly, remove the 8 stainless steel cross head cap screws.

Once the soundome has been filled with oil, keep it in a vertical position to prevent any internal seepage. If the soundome assembly has to be removed for repair or shipment, the oil must always be removed. You may wish to retain the soundome packing material for future use.

Checking Soundome When In Dry Dock

When the vessel is dry-docked, check for any signs of corrosion on the Soundome assembly. Find the reason for the corrosion and as necessary attach a zinc plate to the hull unit as an anticorrosion measure. The soundome cover may be cleaned with a household plastic scouring pad, such as "Scotch Brite" pads.

Please feel free to call us at (360) 834-9300 or visit us on the web at www.Furuno.com if you have any additional questions.

Thank you for purchasing the CH270 Searchlight Sonar System!


Furuno U.S.A., Inc.

IMPORTANT


When installing a sonar or FCV-1200 remember to use the screws on the side of the 25-pin connector (not the rubber boot) to keep the connectors tight.



Not these screws



These screws




TO: All Dealers
RE: CH-270 Erratic targets

We have received a few isolated reports of erratic targets on the CH-270. These problems have been traced to broken wires on the 25-pin J-2 soundome connector. If a wire comes disconnected the soundome may stick in one position. Please check these connections by lightly pulling on the individual wires and resoldering as required.

If you suspect that you are having a problem you can check the soundome by entering the Diagnostics menu and running a Train/Tilt self test.

Pin 1	Red	TI Motor
Pin 2	Blue	TI Phase 1
Pin 3	Black	TI Phase 2
Pin 4	Yellow	TI Phase 3
Pin 5	White	TI Phase 4
Pin 6	Red	TR Motor
Pin 7	White	TR Phase 1
Pin 8	Black	TR Phase 2
Pin 9	Red	TR Phase 3
Pin 10	White	TR Phase 4
Pin 11	Red	TI 93 Degree
Pin 12	White	TI +8 Degree
Pin 13	Red	TR AFT
Pin 14	White	TR Fore
Pin 15	Red	8V
Pin 16	White	0V



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>