

# GP SERIES

## COMMERCIAL / RESIDENTIAL PORTABLE GENERATORS

### FEATURES:

- Generac OHVI® Overhead Valve Industrial Engine With Full Pressure Lubrication and Spin-on Oil Filter
- High performance alternator
- Steel fuel tank with incorporated fuel gauge
- Mobility kit with locking fold-down handles and never-flat wheels
- 1-1/4" diameter hardened steel tube cradle
- Hour meter with maintenance resets
- Electric Start (Includes Starting Battery)
- Circuit breaker protected outlets
- Low-tone muffler

### GP8000E

Model 05681

Running Watts: 8000

Starting Watts: 10,000



| Ratings                        |                            |
|--------------------------------|----------------------------|
| AC Rated Output                | 8.0kW / 8000 Watts         |
| AC Maximum Output              | 10 kW / 10,000 Watts       |
| AC Voltage                     | 120V/240V                  |
| AC Frequency                   | 60 Hz                      |
| 120 VAC Amperage               | Rated 66.6/Max 83.3        |
| 240 VAC Amperage               | Rated 33.3/Max 41.6        |
| Engine                         |                            |
| Engine Type and Displacement   | OHVI Single Cylinder 410cc |
| Oil Capacity w/ Filter Change  | 1.5 Qt. (1.4 liter)        |
| Oil Capacity w/o Filter Change | 1.2 Qt. (1.14 liter)       |
| Low Oil Pressure Shutdown      | Standard                   |

| Fuel                            |                            |
|---------------------------------|----------------------------|
| Fuel Capacity                   | 8.0 Gallons (30.28 liters) |
| Run Time @ ½ Load               | 8 Hours                    |
| Assembled Dimensions and Weight |                            |
| Dimensions L x W x H (inches)   | 33.5 x 26.5 x 27.5         |
| Dimensions L x W x H (mm)       | 850.9 x 673.1 x 698.5      |
| Unit Weight                     | 205 lbs. (92.9 kg.)        |
| Warranty                        |                            |
| Residential                     | 2 Year Limited             |
| Commercial                      | 1 Year Limited             |

Outlets

4 x 5-20R



1 x L14-30R



Maximum wattage and current are subject to, and limited by, such factors as fuel Btu content, ambient temperatures, altitude, engine condition, etc. Maximum power decreases about 3.5% for each 1,000 feet above sea level; and will also decrease about 1% for each 6° C (10° F) above 16° C (60° F) ambient temperature.

**GENERAC**  
POWER SYSTEMS

Generac Power Systems, Inc. • P.O. Box 297, Whitewater, WI 53190 • generac.com

©2008 Generac Power Systems, Inc. All rights reserved. All specifications are subject to change without notice. Bulletin 0178110SBY/Printed in U.S.A. 05.08, rev: 06.08

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>