

IBM System Storage SAN04B-R multiprotocol router



Efficient package with two active Fibre Channel ports and two Ethernet Internet Protocol ports

Highlights

- **Designed for high performance with 4 Gigabit per second (Gbps) Fibre Channel (FC) ports and hardware-assisted traffic processing for line-rate performance across Ethernet Internet Protocol (IP) ports**
- **Utilizes existing Internet, IP-based Metropolitan Area Network (MAN) or Wide Area Network (WAN) infrastructures for metro and global SAN extension for business continuity solutions**
- **Hardware-based compression, large window sizes and selective acknowledgement of IP packets designed to optimize performance of SAN extension over IP networks**
- **Integrated IBM System Storage™ SAN b-type (Brocade) switch management helps simplify installation and administration and helps provide fabric investment protection**

A wide range of IBM System Storage mid-range and enterprise Storage Area Network (SAN) infrastructure simplification and business continuity solutions can be created with the IBM System Storage SAN04B-R multiprotocol router. Infrastructure simplification solutions for the IBM Power™ Systems and System x™ family include disaster tolerance over metropolitan and global IP networks with IBM System Storage disk arrays, tape libraries and IBM Tivoli® Storage Manager data protection software.

Local site infrastructure simplification solutions may be extended to one or more remote sites for enhanced data protection and disaster tolerance. The IBM System Storage SAN04B-R multiprotocol router provides Fibre Channel over IP and FCIP Tunneling Service for distance extension which can enable cost effective and manageable metro

and global business continuity solutions. This extended distance connectivity can help create consolidated remote tape vaulting data protection plus metro mirror and global mirror disk-based disaster tolerant solutions.

High performance

The IBM System Storage SAN04B-R multiprotocol router is designed to deliver 4, 2 and 1 Gigabit per second (Gbps) full-duplex Fibre Channel or 50 Megabit per second Ethernet line-rate performance on all ports. Each router FC port auto-negotiates to 4 or 2 or 1 Gbps depending on the speed of the device at the other end of the link. The Ethernet ports enable reliable SAN extension across the Internet, IP-based Metropolitan Area Networks (MANs) and Wide Area Networks (WANs) through the use of Fast Write, hardware-based compression and storage-optimized protocol enhancements.

High-availability features

Mid-size SAN users require high-availability fabric solutions. The IBM System Storage SAN04B-R multiprotocol router uses second-generation advanced application-specific integrated circuits (ASIC) electronic components to help minimize the number of

components and improve reliability. The SAN04B-R router is designed to provide hot-swappable, load-sharing dual redundant power supplies that allow the router to remain online if one power supply fails. Dual power cords allow attachment to separate power sources for improved availability. Hot-swappable power supplies and redundant cooling fans help eliminate downtime for service when replacing a failed component. Hot-pluggable SFP transceivers are designed to be replaced without taking the router offline.

High availability solutions require redundant components, including clustered servers with dual Host Bus Adapters, dual independent fabrics and disk storage arrays with dual controllers each with dual adapters. Dual IBM System Storage SAN04B-R routers may be configured in a high availability solution to create a resilient "meta" SAN infrastructure.

Configuration flexibility

A variety of SFP transceivers are available to meet diverse requirements. Standard short wave optical Fibre Channel SFPs are available to connect at distances up to 1500 meters. Long wave optical Fibre Channel SFPs are

available to connect at distances of up to 4 km, 10 km or 30 km. Optical SFPs are always used to connect the FC ports to a Fibre Channel fabric, however both optical and copper SFPs are available to connect the Ethernet ports to an Ethernet fabric.

The router helps provide full Fibre Channel fabric services with many standard features including WEBTOOLS with Advanced Zoning, FCIP Tunneling Service and Extended Fabric.

Fabric Operating System

Brocade® Fabric OS® (FOS) is included with each SAN04B-R and contains all functions necessary to operate a base system. The SAN04B-R requires FOS level 6.1.0 or higher. FOS offers the following advanced functions:

- **ADVANCED PERFORMANCE MONITOR** *helps identify end-to-end bandwidth usage by host/target pairs and is designed to provide for capacity planning.*
- **TRUNKING** *enables FC packets to be efficiently distributed across multiple ISLs between two IBM SAN b-type fabric switches and directors while preserving in-order delivery. Both SAN b-type devices must have trunking activated.*

IBM System Storage SAN04B-R at a glance

Product characteristics

| | |
|----------------------------------|--|
| Produce Number | 2005-R04 |
| Base fabric switch | IBM System Storage SAN04B-R multiprotocol router with 2 active Fibre Channel ports, 2 Ethernet IP ports and Brocade Fabric OS (FOS) 6.1.0 or later, hardcopy Installation Guide, CD-ROM (with manuals), service and wrap tools, SFP extraction tool, two 110 volt power cords for rack installation, rail kit, Advanced Zoning, Extended Fabric, Fabric Watch, FCIP Activation, Full Fabric Activation and Web Tools. All active ports must be populated with SFPs. |
| Fibre Channel interface | E_Port, F_Port |
| Optical transceivers | Choice of 4 Gbps short wave, long wave and extended distance long wave (supports 4, 2 and 1 Gbps link speeds) Small Form-Factor Pluggable (SFP). The optical transceivers may be used on any of the ports of the SAN04B-R router (both FC and Ethernet). |
| Copper transceiver | Up to 1 Gigabit per second Ethernet (GbE) (50 MbE on SAN04B-R) |
| Fans and power supplies | Three fans, two power supplies |
| Hot-swappable components | SFP transceivers, fans and power supplies |
| Non-rack support | Non-rack installation is supported; country-specific power cords are required and must be ordered |
| Servers supported* | <ul style="list-style-type: none">• IBM Power Systems, System i™ and selected AS/400® servers, System p™ and selected RS/6000® servers• System x, selected Netfinity® servers and other Intel® processor-based servers• Select Sun™ and HP servers |
| Operating systems supported* | <ul style="list-style-type: none">• Microsoft® Windows® 2000, Windows 2003• Red Hat Linux®, Red Hat Linux Advanced Server• SUSE™ Linux, SUSE Linux Enterprise Server (SLES)• IBM AIX®, HACMP™, i5/OS® and OS/400®• Other selected operating systems |
| Storage Products Supported* | <ul style="list-style-type: none">• IBM System Storage DS8000™, DS6000™ and DS4000™ storage servers• IBM TotalStorage® Enterprise Storage Server® systems• IBM TotalStorage FAST Family of storage servers• IBM System Storage n Series NAS Filers and Gateways• IBM TotalStorage 3580, 3588, 3590, and 3592 tape drives• IBM TotalStorage 3494, 3582, 3583 and 3584 tape libraries• IBM TotalStorage 3581 Tape Autoloader• IBM TotalStorage 3584 High Availability Frame Model HA1• IBM TotalStorage SAN Volume Controller• Other selected storage systems |
| Fibre Channel switches supported | Current IBM System Storage and TotalStorage SAN b-type and m-type switches, routers and directors (must be running current firmware) |
| Fibre optic cable | Fibre optic cables are required and are available in various lengths in single-mode and multi-mode formats |
| Power cords | Jumper cables are included for rack installation; country-specific power cords must be ordered for desktop/standalone installation |
| Warranty | 1-year; Customer Replaceable Unit (CRU); warranty service upgrades are available |
| Optional features | Performance Monitor, Trunking Activation |

IBM System Storage SAN04B-R at a glance

Physical characteristics

| | |
|-------------|---|
| Height | 42.44 mm/1.67 inches |
| Width | 429 mm/16.89 in |
| Depth | 635 mm/25.00 in |
| Weight | 12.43 kg/27.4 lb |
| Temperature | Operating: 0° to 40° C (32° to 104° degrees F) Non-operating: -25° to 70° C (-13° to 158° F) |
| Humidity | Operating: 20% to 85% non-condensing @ 40° C (104° F) Non-operating: 10% to 90% non-condensing at 70° C (158° F) |
| Power | 85 – 264 V AC (Universal), 47 – 63 Hz |

For more information

To learn more about the IBM System Storage SAN04B-R, please contact your IBM marketing representative or IBM Business Partner, or visit:

ibm.com/systems/storage/san/b-type/



© Copyright IBM Corporation 2008

IBM Systems and Technology Group
Route 100
Somers, New York 10589

Produced in the United States
May 2008
All Rights Reserved

IBM, the IBM logo, AIX, AS/400, DS4000, DS6000, DS8000, Enterprise Storage Server, HACMP, i5/OS, Netfinity, OS/400, Power, RS/6000, System i, System p, System Storage, System x, Tivoli and TotalStorage are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries or both.

Brocade and Fabric OS are registered trademarks of Brocade Communications Corporation in the United States and other countries.

Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States, other countries or both.

Intel is a registered trademark of Intel Corporation and its subsidiaries in the United States and other countries.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries or both.

Other company, product and service names may be trademarks or service marks of others. This document could include technical inaccuracies or typographical errors. IBM may make changes, improvements or alterations to the products, programs and services described in this document, including termination of such products, programs and services, at any time and without notice. Any statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only. The information contained in this document is current as of the initial date of publication only and is subject to change without notice. IBM shall have no responsibility to update such information.

IBM is not responsible for the performance or interoperability of any non-IBM products discussed herein. Performance data for IBM and non-IBM products and services contained in this document was derived under specific operating and environmental conditions. The actual results obtained by any party implementing such products or services will depend on a large number of factors specific to such party's operating environment and may vary significantly. IBM makes no representation that these results can be expected or obtained in any implementation of any such products or services.

* For most current and complete details, refer to ibm.com/systems/storage/san/b-type.

TSD03051-USEN-00

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>