

10 WATT GUITAR AMPLIFIER MODEL H6021 INSTRUCTION SHEET



COPYRIGHT © MARCH, 2004 BY GRIZZLY INDUSTRIAL, INC.
WARNING: NO PORTION OF THIS MANUAL MAY BE REPRODUCED IN ANY SHAPE
OR FORM WITHOUT THE WRITTEN APPROVAL OF GRIZZLY INDUSTRIAL, INC.
#6165 PRINTED IN CHINA

MODEL H6021 CONTROLS



- **A. INPUT**: Connect your guitar here, using a shielded instrument cable with a ½" jack.
- B. DRIVE SWITCH: Turns the Drive Channel ON and OFF.
- **C. MASTER VOLUME**: This knob controls the overall volume of the amplifier.
- D. 2 BAND EQUALIZATION: The main equalization of the Model H6021 is a classic 2-band passive network.
- E. HEADPHONE OUTPUT: For connection to almost any headphone with a 1/4" jack.
- **F. POWER SWITCH:** This switch turns the power *ON* and *OFF*.
- **G. POWER LIGHT**: The power light illuminates when the power is *ON*.

Caring For Your Amplifier

- DO NOT remove the grounding prong to fit the plug into a two-pronged outlet!
- To keep the amplifier working properly, DO NOT expose it to rain or moisture.
- DO NOT pull or lift the amplifier by the power cord.
- UNPLUG the amplifier before cleaning, and only clean with a damp cloth (no chemicals).



to fit the plug into a two-pronged outlet!

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com