



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL H0626 OSCILLATING DRILL PRESS

Product Dimensions:

Weight..... 115 lbs.
Length/Width/Height..... 24 x 15 x 38 in.
Foot Print (Length/Width)..... 17-1/2 x 11 in.

Shipping Dimensions:

Type..... Cardboard
Content..... Machine
Weight..... 127 lbs.
Length/Width/Height..... 32 x 19 x 12 in.

Electrical:

Switch..... Paddle On/Off with Safety Lockout Key
Switch Voltage..... 110V
Cord Length..... 9 ft.
Cord Gauge..... 18 gauge
Minimum Circuit Size..... 15 amp
Plug Included..... Yes

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 3/4 HP
Voltage..... 110V
Prewired..... 110V
Phase..... Single
Amps..... 9A
Speed..... 1725 RPM
Cycle..... 60 Hz
Number Of Speeds..... 1
Power Transfer V-Belt Drive
Bearings..... Shielded and Lubricated

Main Specifications:

Construction

Table Construction..... Precision Ground Cast Iron
Spindle Housing Construction..... Cast Iron
Column Construction..... Cylindrical Ground Steel
Head Construction..... Cast Iron
Base Construction..... Cast Iron
Paint..... Epoxy

Head Information

Head Swivel..... 360 deg.

Other Related Information

Base Length.....	17-1/2 in.
Base Width.....	11 in.
Quill Diameter.....	1.565 in.
No. Of Dust Ports.....	1
Dust Port Size.....	2 in.
Depth Stop Type.....	Threaded Rod with Positive Stop
Column Diameter.....	2.79 in.

Spindle Information

Spindle Taper.....	B16
Spindle Travel.....	3-1/4 in.
Dist From Spindle To Column.....	6-3/4 in.
Dist From Spindle To Table.....	17-1/4 in.
Dist From Spindle To Base.....	24 in.

Table Information

Table Diameter.....	12-3/4 in.
Table Thickness.....	1 in.
Floor To Table Height.....	9-1/2 - 21-1/4 in.
Vertical Table Movement.....	Crank Handle Operate
Table Swing.....	360 deg.
Table Tilt.....	90 deg.
Table Swivel Around Center.....	360 deg.
Table Swivel Around Column.....	360 deg.
Maximum Movement Of Work Table.....	11-3/4 in.
No. Of T Slots.....	5
T Slot Width.....	5/8 in.
T Slot Length.....	3 in.

Operation Information

Oscillating Stroke Length.....	3/4 in.
Swing.....	13-1/4 in.
Drilling Capacity.....	3/4 in. in Steel
No Of Spindle Speeds.....	12
Range Of Spindle Speeds.....	250, 330, 380, 500, 590, 640, 980, 1530, 1600, 1870, 2580, 3050 RPM
Drill Chuck Type.....	JT33 Key Chuck
Drill Chuck Size.....	5/8 in.

Other Specifications:

Country Of Origin	China
Warranty	2 Year
Serial Number Location	Data Label on Head
Assembly Time	30 minutes

Features:

- Includes Sanding Kit with 1", 1-1/2", & 2" Drums, Mandrel Washers, and 80 Grit Sanding Sleeves
- Sanding Drum Shaft
- Dust Collection Fitting
- Oscillating Spindle
- 12 Speeds
- 3/4HP Motor
- 1/8" - 5/8" Chuck
- Cushioned Grip Quill Handles

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>