



LCD MONITOR



Display size	22" (55,88 cm) WIDE		
Panel Type	Active Matrix TFT		
Brightness	300 cd/m ² (typ.)		
Contrast (typ.)	800:1		
X-Contrast (dyn.)	-		
Pixel pitch	0,282(H) x 0,282(V) mm		
Resolution (H x V)	WSXGA+ 1680 x 1050		
Response time	5 ms (typ.)		
View angles (CR>10)	H/V 160°/160°		
View angles (CR>5)			
Display colors	16,7 Mio colors		
Display Surface	AG		
Input 1	VGA, Audio		
Input 2	DVI-D		
Input 3	Component Input		
Headphone			
Speakers	3 W x 2		
Supply	AC 100~240V, 50~60Hz		
Consumption	On:	49 W	Stand-by: Off:
Operation Temp/Hum	0 ~ 40°C		10 - 85%
Dimension (W*D*H)	520 x 206 x 410 mm		
Net weight	6,8 kg		
Tilt	0°~ 20°		
Kensington Lock	✓		
VESA mounting	VESA Standard, 100mm		
On screen display	EN,TC,DE,FR,ES,IT,PT,NL,SC,JS,KR		
Safety	CE, FCC, BSMI, C-Tick, VCCI, CB, UL/CUL, BAU-MARK, CCC, MIC		
Emission	TCO03		
Power saving	EnergyStar		
Extras 1	USB2.0 Hub (4x)		
Extras 2			
Extras 3			
EAN	4710859554710		
incl Accessory	Power cord, VGA cable, DVI-D cable, Audio cable (3.5mm jack), Audio cable (cinch, 3.5mm jack), component-DVI adapter		



© HANNspree Europe GmbH. Information in this document is subject to change without notice. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Screenshots are simulated.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>