

Models: WHB30, WHB33, WHB36, WHB42 WTB30, WTB33, WTB36, WTB42

These refractories are intended for use with the Novus NDV and NBV Series gas appliances. Check with your local building code agency before you begin installation to ensure compliance with local codes, including the need for permits and follow-up inspections. If you encounter any problems regarding code approvals, or if you need clarification of any of the instructions contained here, contact your Hearth & Home Technologies Inc. dealer. For the dealer nearest you, please visit www.heatilator.com

Note: An arrow (⇒) found in the text signifies change in content.



1. Shut off the electricity to the appliance and turn the gas shutoff valve to the closed position. See Figure 1. Remove the screen and glass from the appliance.



- 2. If installing this refractory into a B-Vent Appliance, please go to "To Convert Refractory Kit to Fit B-Vent Appliance" on page 4 of this manual.
- **3.** Attach the two long hook-shaped brackets by removing the two outside screws on the false back and reinstall the screws. See Figures 2 and 3.



Figure 2 Location of Hook-Shaped Brackets



Make sure to shorten the bracket if installing in a B-vent unit. See Figure 4.



4. Set the back refractory piece into the brackets. See Figures 5 and 6.



Figure 5 Position Back Refractory for Placement



Figure 6 Set Back Refractory in Place

5. If lava rock has been placed in appliance, clean the rock away from the firebox sides to make room for the side refractory. See Figure 7.



6. Carefully install a side refractory. See Figures 8 and 9.





Figure 9 Set Side Refractory in Place

7. To secure the side refractory in place, remove either the middle or back screw in the firebox top. Attach a refractory bracket (using the screw removed) to the firebox top. See Figure 10.



 Repeat Step 3 to install the other side refractory piece. See Figure 11.



- 9. Adjust the back and sides so no gaps are visible in the corners where the pieces come together.
- 10. Repeat Step 7. to install the other side.
- 11. Reinstall the fixed glass assembly and screen.
- 12. Restore power and gas flow. Your refractory installation is now complete.

12. Convert Refractory Kit to Fit B-Vent Appliance

a. Locate the back refractory piece and lay the brick side down on a flat surface. Locate the indicator marks on the back of the refractory piece. Lay a straight edge on the indicator marks and cut with a utility knife. See Figure 8.



- b. B-Vent/Herringbone cut at line, discard lower (smaller) portion. Install cut side down. Refer to Figure 9.
- c. Direct Vent/Herringbone Install whole refractory.



- d. B-Vent/Traditional cut at line, discard upper (smaller) portion. Install cut side down. Refer to Figure 10.
- e. Direct Vent/Traditional Install whole refractory.

	(back of Traditional refractory)
	(bottom for b-vent)
Figure 10	

Heatilator • WHB/WTB Refractory • 4055-186 Rev C • 03/08 Download from Www.Somanuals.com. All Manuals Search And Download.

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com