HP Digital Projector xp8000 series





Deliver professional presentations with the HP Digital Projector xp8000 series which gives you bright, sharp images with rich colours and the benefit of wireless connectivity. What's more, its advanced features are easy to understand and use.

The ideal solution for businesses, organisations, government and educational institutions that need a high-end projector that is easily installed and maintained, enabling them to present high quality, worry-free professional presentations flexibly in a wide variety of environments and lighting conditions.



HP Digital Projector xp8010

High brightness, vibrant colours and a choice of lenses enable you to project in almost any space.

- High brightness of 2600 lumens¹ or a powerful 3100 lumens² ensures vivid images and the flexibility to present in different lighting conditions.
- Colours have never been brighter thanks to expert colour matching, enhanced colour tables, a patented dual colour wheel, XGA resolution and a high contrast ratio.
- · Adjust the projection distance and fit the image to any size space with the easily angled, short, medium, and long throw lenses.
- Mount it to the ceiling, on a rear wall, or keep it portable.

Present with confidence using advanced features which are easy to understand and use.



HP Digital Projector xp8020

- Take the stress out of presenting as the projector's intuitive interface facilitates set-up and use, and settings are simple.
- · Maximise the impact of presentations with the video and audio options which are easy to find, set and run.
- Keep control with the intuitive, laser-equipped remote control which provides access to all the features the projector offers.
- Top-loading means the lamp is easy to reach and replace as needed, no matter where the projector is mounted.

Flexible networking connectivity lets you manage and run presentations to and from almost anywhere.

- Present wirelessly from a PC or pocket PC, over the network, or directly from a CompactFlash™ memory card³.
- Work with anyone on your LAN using internet-based collaborative tools.
- Protect your equipment from theft with an automatic e-mail alert as soon as the projector is removed from network or power3.
- Data content is protected by an enhanced-security wireless protocol.
- · Manage projectors over the network; adjust settings, receive automatic warnings, set passwords, update firmware from anywhere.



¹HP Digital Projector xp8010

²HP Digital Projector xp8020

³ Theft protection and presentation from storage require future firmware upgrade. Check for availability on www.hp.com or with your local HP reseller.

Technical specification	NS .	Orde	ring information
Brightness	HP Digital Projector xp8010: 2600 ANSI lumens (peak), 3600 lumens in greyscale HP Digital Projector xp8020: 3100 ANSI lumens (peak), 3850 lumens in greyscale	L1575A HP Digital Projector xp8010; AC 3-conductor power cord, 3 m; VGA cable; wireless remote control	
Display resolution	Native XGA (1024 x 768)		
Resolutions supported through scaling	VGA to UXGA (640 x 480 to 1600 x 1200); HDTV (up to 1080i) and Mac compatible; NTSC, PAL, and SECAM compatible	poin	with mouse function and lase ter; multi-language user's guide
Dimensions (w x d x h)	Out of package: 400 x 275 x 130 mm without handle, focus ring, feet; 442 x 304 x 139 mm with handle, focus ring, feet	(ČD-ROM); multi-language quick state card; 2 batteries; lens cap; cabl shroud, warranty can be shroud, warranty can be shroud, warranty can card; 2 batteries; lens cap; cabl shroud, warranty can be shroud, warranty candidate and candidate context. With mouse function and laser pointer multi-language user's guid (CD-ROM); multi-language quick state card; 2 batteries; lens cap; cabl	
Weight	Out of package: HP Digital Projector xp8010: 6.0 kg; HP Digital Projector xp8020: 6.1 kg		
Images technology	DLP" (0.7" 12° DDR); HP patented dual colour wheel technology with 4 segment (RGBW) data and 6 segment (RGBRGB) video colour wheels		
Image contrast	HP Digital Projector xp8010: JBMA 800:1 (full-on/full-off); ANSI 350:1 (checkerboard)		
Noise level	Normal operation: 32 dB(A) ±2 dB(A), under 25° C peak: 34 dB(A) peak		
Colour	24-bits, 16.8 million colours		
Lens	F/2.0 ~ 2.4, f=28.6 ~ 34.3 mm with 1.2x manual zoom lens		
Projection size	Approximately 0.9 to 7.5 m		
Throw distance	Approximately 1.5 to 12 m (standard lens)		shroud, warranty card
Offset	±100%		Lamp
		L1582A	<u> </u>
Keystoning	Horizontal ±17° (34° total), vertical ±40° (80° total) Advanced electronic keystone correction		250 watt comp P-VIP bulb – xp8010
User interface	Wireless remote controller with USB mouse function and laser pointer Lamp broken – red; temperature warning – red; power – blue User-friendly multilingual On Screen Display (OSD)	L1583A	300 watt comp P-VIP bulb – xp8020
	Power, Theatre video mode select, Greyscale mode select, Presentation mode select, Menu select, Menu right, Menu left, Menu up, Menu down, Source select, Autosync		Cables
Certifications	USA: EMC – FCC Part 15 Class B, Safety – UL950, RF – FCC part 15 C, Safety – FDA (remote controller); Canada: EMC – ICES-003 Class B, Safety – CSA 22.2 #60950, RF; UK/Germany/Italy/Switzerland/France/Austria/Sweden/Finland/Denmark/Norway/Spain/Netherlands/Arab Emirates/Belgium/Greece/South Africa/Portugal/Ireland/Luxembourg/Slovakia: EMC, German Safety (IV-GS), Safety, CB, RF; Czech Republic: IEC 60950, EN 55022, EN 55024; Malaysia/Philippines/Thailand/India/Indonesia/Vietnam/Taiwan: EMC/Safety; Taiwan: RF; Japan: EMC-ITE Class B/CISPR22, Safety - IEC 60825 for remote controller, RF- ARIB STD T-66/STD 33; China: GB9254-1988,GB17625.1-1998, GB4943-1995, RF; Korea: EMC-CISPR22, Safety, RF; ANZ: EMC-AS/NZS 3548: 1992, Safety, RF; Singapore: IEC 60950/Sing. Deviation, RF; Mexico: NOM +171; Argentina: IEC 60950; Columbia/Chile/Venezuela/Central America/Peru/Ecuador: EMC, Safety, RF; Hong Kong: EMI	L1514A	Cable VGA/USB-to-M1-AD - 1.8 m
		L1529A	Cable DVI/USB-to-M1-AD - 1.8 n
		L1588A	Cable SCART-to-M1-AD - 1.8 n
		L1589A	Cable BNC-to-M1-AD – 1.8 n
Audio	5 watt stereo with acoustic chambers		Connectivity
Computer compatibility	UXGA, SXGA, XGA+, XGA, SVGA, VGA, Mac, Mac LC 13 inch, Mac II 13 inch, Mac 16 inch, Mac 19 inch, Mac G4, iMac DV	L1581A	Advanced Connectivity
Video/audio interfaces	M1-DA/mini phone plug; VGA input (2x)/mini phone plug (2x); VGA output/stereo RCA; S-video input/stereo RCA; composite video input/stereo RCA; component video input – 3 RCA (YPbPr)/stereo RCA; BNC (RGsB, RGBB), RGBHY, YPbPr)/stereo RCA	L1640B	Module – xp8010 802.11b CompactFlash -
Video compatibility			Channel 1-13
<u>' '</u>	VGA, DVI, S-video, Composite video, Component video, BNC		
External I/O Ports	HP Digital Projector xp8010: Standard Connectivity Module: USB (compatible with USB 2.0 specifications) Type B for remote; LAN (R45); Control (R5232) HP Digital Projector xp8020: Advanced Connectivity Module: 2 x USB (compatible with USB 2.0 specifications) Type B for	L1578A	Other accessories Lens Ultra wide angle
	keyboard/mouse; LAN (RJ45); Control (RS232); 2 x Type-II CompactFlash slots for wireless (ad-hoc/infrastructure) connectivity or	or	1.67:1 to 2.0:1
	presenting from storage device	L1580A	Lens Long throw 2.4:1 to 2.88:1
Power	100-120 V, 200-240 V at 50-60 Hz; battery backup for time/date	L1584A	
Lamp	HP Digital Projector xp8010: 250 watt P-VIP lamp (1.3 mm); 2,000 hours life, 4,000 hours in lamp saver mode HP Digital Projector xp8020: 300 watt P-VIP lamp (1.3 mm); 2,000 hours life, 4,000 hours in lamp saver mode		Soft Carry Case - xp8000 serie
	Lamp power supply is automatically shut-off when door is open	L1585A	Hard Carry Case - xp8000 serie
Operating environment	Operating temperature: 10 to 40° C; operating humidity: 80% RH (max, 10 to 40° C, non-condensing)	L1590A	Ceiling Mount -
Mounting capability	Ceiling, tripod, tabletop	L1370A	xp8000 series
Warranty	3 year pick-up and return for Europe, Middle East and Africa. 90 day standard bulb warranty. Within the bulb warranty period, defective bulbs will be replaced via overnight shipment.	L1586A	Remote Control, Wireless (IR) Smar
		L1642A	Cable Extended IF Receiver – 15 n
		L1646A	Gyration RF Remote Contro
		L1671A	Screen, 50" Presente
		LIO/ IA	Scieen, 30 riesenter

http://www.hp.com

For more information, please call your local HP sales office or representative: **Austria**: 0800 242 242, **Algeria**: (0)61 56 45 43, **Bahrain**: 800 728, **Belgium**: (078) 15 20 30 (0.0496 EUR/min), **Bulgaria**: (+359) 2960 1940, **Croatia**: (+385 1) 60 60 200, **Czech Republic**: (90 420 2) 261 108 108 (Prague), **Denmark**: 48 12 10 00, **Egypt**: 532 5222, **Estonia**: (+372) 6813 823, **Finland**: (+358) 0205350 or 0205 350, **France**: (1) 69 82 6060, **Germany**: 0180 532 6222 (12 Cent/min), **Greece**: (01) 678 96 00, **Hungary**: (+36) 1 382-1111, **Iceland**: (354) 570 1000, **Ireland**: +353 1 6158200, **Israel**: (972) 9 8304848, **Italy**: (02) 92121, **Kazakhstan**: +7 (3272) 980 824, **Latria**: (371) 800 80 12, **Lithuania**: 8 800 10000 or 8 5 2103333, **Luxembourg**: (+352) 263 160 34, **Middle East**: 00971 4 883 4427, **Morocco (African Region**): +212 22 40 47 47, **Netherlands**: (020) 5476666, **Norway**: 22 735600, **Poland**: infolinic: -800 124 622, **Portugal**: (808) 206 001, **Romainia**: (+401) 205 3300, **Rossia**: +7 (95) 797 35 00, **Soudi** Arabia: 800 124 4046, **Serbia/Montenegro**: +381 11 201 99 00, **Slovakia**: +421-2-50222111, **Slovenia**: +3861 2307 420, **South Africa**: 0800 118 883, **Spain**: (91) 634 88 00, **Sweden**: (08) 444 2000, **Switzerland**: 0848 88 44 66, **Tunisia**: 71 891 222, **Turkey**: +90 (216) 579 71 71, **UAE**: 8004910, **UK**: 08705 474747, **Ukraine**: +380 44 490 61 20.

DLP™ technology by Texas Instruments offers crystal clear images with superior quality









©2004 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com