



# FasTrak™ Super Duty 48/54/60

**NEW!**  
**60" DECK**  
**MODEL**

### Features and Benefits

- Kawasaki Commercial V-twin engines
- Welded steel decks. NOT STAMPED!
- 20" drive tires, 13" caster tires
- Commercial hydrostatic transmissions for true zero turning radius maneuverability
- Commercial duty, serviceable deck spindles
- Heavy-duty, remote air cleaner for increased engine protection.
- Heavy-duty, 7-gauge, full-height rear bumper with built-in hitch provides protection for the engine and exhaust, retains the ease of maintenance.
- Toughest frame, front forks, and deck in the industry
- Wide stance, low center of gravity for unmatched stability on slopes
- Simplest maintenance in the industry
- 10-gallon fuel capacity with built-in sight line
- Seat springs and slide with arm rests come standard
- Silky-smooth SmoothTrak™ steering with patented automatic park brake system
- Optional, foldable certified ROPS and seat belt.
- 48", 54" or 60" side-discharge/mulching decks
- "Drive-straight" adjustment.
- Standard hour meter.

(Mower shown with optional ROPS)



### Best warranty in the business

- Lifetime warranty on the leading edge of the deck
- Lifetime warranty on tractor frame
- A limited residential four-year warranty – parts and labor\*
- A limited 2-year commercial warranty – parts and labor\*

\*See your local Hustler dealer for complete warranty details





# The FasTrak™ Super Duty Specifications 48/54/60

(Mower shown with optional ROPS)



**Starter** 12-volt (.8 kw) (see engine manufacturer specs)

**Ignition** Electronic

**Charging System** 12-volt, 15-amp (see engine manufacturer specs)

**Fuel** Unleaded gasoline (see engine manufacturer specs)

**Fuel Filter** Replaceable, automotive-type

**Air Cleaner** Heavy-duty, remote mounted

**Cooling** Air cooled. Fly-wheel fan

**Governor** Mechanical

#### Traction Drive System

**Type** Dual hydrostatic. Commercial-duty Hydro-Gear ZT 2800. ZT transmissions feature relief valve, charge pump, spin-on oil filter, expansion tank, and steel cut gears. Hydraulic system operates on 20W50 motor oil.

**Hydrostatic Drive** V-belt drive from engine crankshaft

**Ground Speed** Infinitely variable: 0-8 mph (0-12.9 kph) forward, 0-5 mph (0-8 kph) reverse

**Steering** Twin-lever SmoothTrak™ steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with hand-operated controls

**Turning Radius** True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels

#### Brakes

**Service:** Hydrostatic dynamic braking

**Parking:** Internal transmission mechanical brake. When steering levers are placed in neutral position, integral park brakes are automatically engaged

**Mower Drive** Single V-belt drive from engine with electric clutch. Spring tension idler for extended belt life

#### Tires

**Front:** 13 x 5 – 6, rib tread

**Drive:** 48 in: 20 x 10 – 10, turf tread

54 in: 20 x 12 – 10, turf tread

**Capacities Fuel System:** 10 US gal (37.85 l)

#### Dimensions

**Height:** 41.8 in (106.17 cm)

#### W/48 in Deck

**Length:** 74.42 in (189.02 cm)

**Overall width:** 51.77 in (131.50 cm) w/discharge chute up

**Tire-to-tire width:** 47 in (119.38 cm)

**Weight:** 835 lbs (378 kg)

#### W/54 in Deck

**Length:** 74.42 in (189.02 cm)

**Overall width:** 61.30 in (155.70 cm) w/discharge chute up

**Tire-to-tire width:** 51 in (129.54 cm)

**Weight:** 860 lbs (390 kg)

## FasTrak™ Super Duty 48/54/60 Specifications

### Engine

Model	23/48	25/54	25/60
Make	Kawasaki	Kawasaki	Kawasaki
Horsepower	23	25	25
No. of Cylinders	2	2	2
Max. Torque	39.8 ft lbs @ 2400 rpm	41.2 ft lbs @ 2400 rpm	41.2 ft lbs @ 2400 rpm

### W/60 in Deck

**Length:** 75.92 in (193 cm)

**Overall width:** 66 in (168 cm) w/discharge chute up

**Tire-to-tire width:** 51 in (129.54 cm)

**Weight:** 885 lbs (401 kg)

**Safety Features** Operator presence system connected to deck and drive clutches. Stabilizer rollers at rear of tractor

**Seat** Molded, cool-grey vinyl seat with adjustable armrests. Fore and aft sliding adjustment. Seat-pan suspension springs standard.

**Construction** Mainframe is 1.5 in x 1.5 in x .188 in (3.8 cm x 3.8 cm x .48 cm) square steel tubing. Front caster wheels mounted with roller bearings on each wheel. Front caster forks are .375 in (.95 cm) steel

**Deck Lift** Foot-operated deck height adjustment. Pin for setting height, detent for transport position

**Controls** Hand-operated choke, throttle, ignition switch, electric mower clutch. Integrated parking brakes

**Indicators** Engine warning light (low oil pressure)

**Cup Holder** Two cup holders molded into the left side fuel tank. Accommodates nearly any cup size.

**Decks** 48", 54" or 60" Side-Discharge Decks

**Type** Free-floating mower using three blades with center blade to the front. Mower is suspended at the corners. Includes 4 deck-mounted rollers to improve flotation in rolling and uneven terrain

**Deck Lift** Raise and lower deck from driver's seat with simple foot-operated deck height adjustment. Pin for setting height, transport position. Change cutting heights, hop curbs and trailer more easily

**Construction** .125 in (.317 cm) welded steel. Solid 1 in x .375 (2.55 cm x .95 cm) steel bars reinforce impact areas on trim edges. Commercial-style box-section reinforced front edge. Reinforcements welded onto spindle mount areas. Molded rubber discharge chute.

**Cutting Heights** Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.5 in to 4.5 in (3.81 cm to 11.43 cm)

**Mowing Blades** Heavy-duty, heat-treated, high-lift Fusion™ blades

48 in: 16.5 in x 2.5 in x .20 in

54 in: 18.5 in x 2.5 in x .20 in

#### Blade Tip Speed

48 in: 18,306 fpm (at 3500 RPM engine speed)

54 in: 18,464 fpm

60 in: 18,331 fpm

**Blade Drive** V-belt drive to all three spindles. Spring tension idler pulleys. Spindles Aluminum casting with steel shafts and sealed ball bearings

**Flotation** Suspended mower floats on four spring-assisted chains. 4 anti-scalp wheels are standard

### Width of Cut

48 in: 47.1 in (120 cm)

54 in: 53.1 in (135 cm)

60 in: 59.1 in (150 cm)

### Trim Capacity (left side)

48 in: 0.5 in (1.25 cm)

54 in: 2.5 in (6.5 cm)

60 in: 5.9 in (15 cm)

### Accessories

**Flex Forks™** Shock-absorbing front caster forks for a smooth ride and smoother cut

**Mulch Kit** Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil

**Catcher** Commercial-duty, 6.5 bushel, rear-mounted, two-bag catcher

**ROPS** Certified, 2-post, foldable ROPS

**Stripe Kit** Make your lawn look like Yankee stadium

**Personalized Bumper** Have your name laser-cut into the rear bumper of your mower. Ask your dealer for details.

**Snow Blower** 48", two-stage blower utilizes the deck-lift to raise and lower. The blower is powered by deck belt and features a rotating chute adjustable from the seat and a heavy-duty gear box

**Snow Blade** 56" wide, 3-position angling, heavy-duty, reversible, replaceable cutting edge

**Gator™ Blades** Patented mulching blade design

**Wavy Blades** Improved performance for mulching

**Jack Kit** Mounts to unit and can be carried onboard at all times

**Other Accessories** Light Kit, Tire Chains, Steering Lever Extension Kit, Weight/Utility Box

*Specifications subject to change without notice.*



For more information : [www.hustlerturf.com](http://www.hustlerturf.com) **HUSTLER**

HUSTLER TURF EQUIPMENT • HESSTON, KANSAS 67062 • 1-800-395-4757

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>